

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7257)

Set a stone 15 x 12 x 6 ins., 10" in the ground for $\frac{1}{4}$ sec.cor. marked $\frac{1}{4}$ on N. face, from which

A Fir 16" dia., bears N.36°E., 20 lks. dist. mkd. $\frac{1}{4}$ S BT

A Fir 22" dia., bears S.25°E., 31 lks. dist. mkd. $\frac{1}{4}$ S BT

BLM resurvey by John Jelley, Cadastral Surveyor, Group #571, surveyed May/June 1965 - (DCSO records Vol. 33 Page(s) 13868-69)

Point for the $\frac{1}{4}$ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 30 S R 7 W

$\frac{1}{4}$ $\frac{S \ 10}{S \ 15}$
1965

from which

A Fir 9" dia., bears N.10 $\frac{1}{2}$ °E., 32 lks. dist. mkd. $\frac{1}{4}$ S10 BT

A Fir 11" dia., bears S.57°E., 52 lks. dist. mkd. $\frac{1}{4}$ S15 BT