

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 3; & S 34, T29 1/2-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 - Survey dated July 28, 1882 (DCSO records, Vol. 15 Pg. 6550)

Set a Fir post, 4 ft. long, 4" square, 20" in ground, for the 1/4 sec. corner, marked 1/4 S. on the N. face, from which,
A Fir 18" dia., bears S.20°E., 19 lks. dist. marked 1/4 S. BT.
A Pine 18" dia., bears N.48°W., 122 lks. dist. marked 1/4 S. BT.

GL0 survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 6053)

Intersect the point for 1/4 sec. cor. located by measurement from the original bearing trees.

At the exact cor. point
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked:

S34
1/4 T29 1/2
 S3
 1924

from which the original bearing trees:
A Fir 32" dia., bears S.20°E., 19 lks. dist., marked 1/4 S BT. on the bark.
A Pine stump bears N.48°W., 122 lks. dist., blaze shows.
New Bearing trees:
A Fir 18" dia., bears S.54°E., 61 lks. dist., marked 1/4 S3 BT.
A Fir 16" dia., bears N.78°W., 36 lks. dist., marked 1/4 S34 T29 1/2 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - June 1962 - C.S. File 49/139-86

Found - Brass cap at corner and NW BT.
 SE BT, now stump.
New BT - 14" R.Fir bears S.43°E., 41.6 ft. scribed 1/4 S3 CS BT

Fd. OK, Howard Johnstone, Oct. 1980 - M 86-77