TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35; 2 & 3, T31-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7229)

Set post corner to secs. 2, 3, 34 and 35, from which
A Pine 18" dia., bears N.63°E., 212 lks. dist.
A Pine 12" dia., bears S.82°E., 139 lks. dist.
A Pine 15" dia., bears S.85°W., 30 lks. dist.
A Pine 24" dia., bears N.60°W., 292 lks. dist.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell, crew - Dec. 27, 1962 - C.S. File ~~49/139~~ 49/109-14 (6/13/2022)

Found - Orig. 15" now 26" Pine, S.85°W., 19.8 ft., shows good scribing.
Orig. 24" now 38" Pine snag, shows old axe work, N.63°E., 139.9 ft.
Other orig. BTs, not found.

Set Brass cap at cor. mkd: County Surveyors Office

S34	S35	T30S	R7W
S 3	S 2	T31S	

1962

New BTs -23" Cedar bears N.30°E., 13.6 ft. scribed S35 T30S R7W CS BT.
12" Pine bears S.31°E., 8.7 ft. scribed S2 T31S R7W CS BT.
8" Pine bears N.3°W., 47.3 ft. scribed S34 CS BT.

Cor. Fd. and used in BLM resurvey by James Jelley, Under Group #'s 350 and 680, surveyed April/Sept. 1969 - (DCSO records Vol. 35 Page 14501) and June 1977 - (DCSO records Vol. 41 Page 16244 and Pg. 16261)

Fd. OK, Oct. 1984 by H. Johnstone - M 97-61

DCSO-GIS Corner visitation - 2/2/2004 - Typed: 2/10/2011 - C.S. File 67/33-1

Monument - 1¼" IP/BC