

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7238)

Set ¼ sec. post, from which
A Pine 14" dia., bears N.85°E., 75 lks. dist.
A Pine 24" dia., bears S.86°W., 125 lks. dist.

Renewed corner by Norman D. Price, LS #33 - April 25, 1953 - C.S. File 41/151

The ¼ sec. cor. of secs.34 and 35 is monumented with the decayed remains of a wooden stake, firmly set in a mound of stone; from which the original bearing trees are as follows:
A Yellow Pine 32" dia., bears N.85 3/4°E., 49.2 ft. dist., with the scribe marks ¼ S uncovered and the lower blaze healed.

A Yellow Pine 36" dia., dead and down, bears S.79 3/4°W., 78.8 ft. dist., with old blazes burnt.

At the corner point

Set an iron post, 3 ft. long, 1½" dia., 4" in the ground to bedrock, and in a mound of stone to top, mkd. RS33; from which a new bearing tree:

A Yellow Pine 14" dia., bears N.81½°W., 18.8 ft. dist., mkd. ¼ S34 RS33 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell, crew - May 22, 1963 - C.S. File 49/139-102

Found - 1" x 30" I.P. at cor. and in mound of rock. Corner pipe has wood plug and bronze cap stamped RS.
16" Pine stump bears N.83°W., 19.0 ft., shows scribing near base, not old.
Orig. 14" now 24" Pine N.85°E., 49.5 ft., previously opened, shows good scribing.
Orig. SW. BT not found.

New BT - 12" Pine bears N.10°W., 9.8 ft. scribed ¼ S34 CS BT.
Corner pipe is on solid rock.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #897, surveyed Sept. 1976/June 1977 - (DCSO records Vol. 41 Page(s) 16245-46)

The ¼ sec. cor. perpetuated and recorded by Price in 1953, and further perpetuated by Byron in 1962, monumented with an iron pipe, 1" dia., firmly set, projecting 12" above ground, (Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and in a mound of stone, 3 ft. base, to top, with a bronze washer on top, mkd. RS 33, from which the remains of the original bearing trees:

A Pine 35" dia., bears N.85°E., 75 lks. dist., with fragmentary scribe marks visible on open blaze.

A root hole bears S.80°W., 125 lks. dist., with a down Pine alongside, 36" dia., no marks visible.

and the remains of a bearing tree mkd. by Price:

A sawed Pine stump 16" dia., bears N.82°W., 30 lks. dist. with fragmentary scribe marks visible on open blaze.

and a bearing tree mkd. by Byron:

A Pine 14" dia., bears N.12 3/4°W., 15 1/2 lks. dist. with scribe marks 1/4 S34 CS BT visible on open blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

1/4
S 34 | S 35
T 30 S R 7 W
1976

Reset Iron pipe alongside iron post.

Fd. OK, March 1994 by R. Quimbly - M 119-21