

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7239)

Set ¼ sec. post, from which
A Pine 8" dia., bears S.35°E., 194 lks. dist.
A Pine 10" dia., bears S.80°W., 175 lks. dist.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1007, surveyed Aug. 1980/March 1982 - (DCSO records Vol. 43 Page(s) 16793)

The ¼ sec. cor. of secs. 26 and 27, determined at record bearing and distance from the remaining original bearing tree:

A Pine 28" dia., bears S.35°E., 194 lks. dist., with fragmentary scribe marks visible on partially opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap

mkd: T 30 S R 7 W
1/4
S 27 S 26
1980

from which new bearing trees:

A Pine 15" dia., bears S.25½°E., 146 lks. dist. mkd. ¼ S26 BT.

A Fir 10" dia., bears S.4½°W., 116 lks. dist. mkd. ¼ S27 BT.