

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7239)

-----  
Set post cor. to secs. 22, 23, 26 and 27, from which  
An Alder 8" dia., bears N.50°E., 281 lks. dist.  
An Alder 10" dia., bears S.20°E., 375 lks. dist.  
A Pine 8" dia., bears S.35°W., 461 lks. dist.  
An Oak 24" dia., bears N.28°W., 200 lks. dist.

Survey by R. Ware - For: Dean Sanders - April 1975 - M 57-3

-----  
Found - 30" Oak fallen over, N.28°W., 132.0 ft. Old fce and chop marks, grown over.  
Set Brass cap mkd. T30S R7W WM L.S. No. 1005 22, 23, 27, 26.  
New BTs -7" Fir N.57°W., 80.6 ft. scribed S22 BT.  
8" Fir S.70°W., 147.7 ft. scribed S27 BT.  
13" W.Oak scribed S26 BT, S.65½°E., 59.1 ft.  
24" Cedar scribed S23 BT, N.41°E., 153.2 ft.

Revised survey by R. Ware - For: Dean Sanders - July 1975 - M 57-52

-----  
Brass cap set April 1975 was replaced with a 1¼" I.Pipe in July 1975. Brass cap set at proper section corner bears S.50°40'35"W., 107.19 ft. from 1¼" I.P. (Corner double proportioned).  
The bearing trees described previously are now from the iron pipe and described as follows:  
8" Fir scribed "S27 BT" bears S.70°W., 147.7 ft.  
7" Fir scribed "S22 BT" bears N.57°W., 80.6 ft.  
30" Oak, fallen over, old face and chop marks grown over, bears N.28°W., 132.0 ft.  
24" Cedar scribed "S23 BT" bears N.41°E., 153.2 ft.  
13" W.Oak scribed "S26 BT" bears S.65½°E., 59.1 ft.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #1007, surveyed Aug. 1980/March 1982 - (DCSO records Vol. 43 Page(s) 16794)

-----  
Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.     T 30 S     R 7 W  
                          S 22     S 23  
                          S 27     S 26

1980

(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which  
A Cedar 26" dia., bears N.43°E., 391 lks. dist. mkd. T30S R7W S23 BT.  
A Cedar 5" dia., bears S.63¼°E., 239 lks. dist. mkd. X BT.  
A Fir 19" dia., bears S.66°W., 174 lks. dist. mkd. T30S R7W S27 BT.  
A Fir 6" dia., bears N.43¼°W., 71 lks. dist. mkd. T30S R7W S22 BT.

BLM report of field corrections - Filed March 11, 1982 in C.S. File 61/33-1

-----  
Corner point from double proportion. Corner point accepted by Jake Jelley in 1980 was moved to proportion point, S.49°08'W., 1.611 chs. Brass cap as established by R.Ware, was pulled by Ware and will use ours. (BLM)