

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7240)

-----  
Set post cor. to secs. 14, 15, 22 and 23, from which  
A Fir 14" dia., bears N.24°E., 114 lks. dist.  
A Laurel 14" dia., bears S.80°E., 82 lks. dist.  
A Laurel 60" dia., bears S.48°W., 67 lks. dist.  
A Cedar 12" dia., bears N.28°W., 67 lks. dist.

Cor. Fd. and used in GLO resurvey by W.H. Byars, under Contract #450, dated July 28, 1882 - (DCSO records, Vol. 17 Page 7258)

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman crew - Feb. 1964 - C.S. File 53/40-44

-----  
Found - Orig. 60" now 50" Laurel S.48°W., 15.2 ft., shows good scribing.  
Orig. 14" now 36" Fir snag N.24°E., 75.2 ft., shows scribing.  
Orig. SE. BT in slide area.  
Now 30" Cedar N.18°W., 44.2 ft., not N.28°W., 44.2 ft., shows faint scar.

Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 7 W  
S 15 | S 14  
S 22 | S 23  
1964

New BTs -11" R.Fir bears S.64°E., 25.8 ft. scribed S23 T30S R7W CS BT.  
6" R.Fir bears S.48°W., 5.5 ft. scribed S22 CS BT.  
14" R.Fir N.26°E., 28.2 ft. scribed S14 T30S R7W CS BT.  
30" Cedar bears N.18°W., 45.7 ft. scribed S15 T30S R7W CS BT.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #571, surveyed May/June 1965 - (DCSO records Vol. 33 Page(s) 13860-61)

-----  
The Sec. cor., perpetuated by the County in 1964, monumented with an iron post, 1" dia., firmly set, extending 12" above the ground, with properly mkd. brass cap, from which the remaining original bearing trees:  
A Fir snag 42" dia., bears N.26°E., 120 lks. dist. with scribe marks S T visible on burned and rotted blaze.  
(Record, N.24°E., 114 lks.) (Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A Madrone 45" dia., bears S.48°W., 24½ lks. dist., with scribe marks 22 S W visible on partially healed blaze. (Record 23 lks.)

A Cedar 30" dia., bears N.18°W., 68 lks. dist., has been remarked T30S R7W S15 CS BT on double blaze. (Record, N.28°W., 67 lks.)

and County Surveyors bearing trees:

A Fir 13" dia., bears N.26°E., 43 lks. dist., with scribe marks T30S R7W S14 CS BT visible on double blaze.

A Fir 12" dia., bears S.65°E., 39 lks. dist., with illegible scribe marks visible on partially healed double blaze.

A Fir 6" dia., bears S.48°W., 8½ lks. dist., with scribe marks S22 CS BT visible on partially healed double blaze.

Add marks BLM 1965 to brass cap.