

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7241)

-----  
Set post cor. to secs. 10, 11, 14 and 15, from which  
A Laurel 12" dia., bears N.40°E., 33 lks. dist.  
A Laurel 14" dia., bears S.10°E., 16 lks. dist.  
A Laurel 14" dia., bears S.60°W., 56 lks. dist.  
A Laurel 40" dia., bears N.65°W., 33 lks. dist.

Fd. Cor. OK, in GLO survey by W.H. Byars, Contract #450, dated July 28, 1882 - (DCSO records, Vol. 17 Pg. 7257 & 7258)

Douglas County Surveyors Office - Vernon R. Tracy; Mike Darby; Jack Barnett, crew - Aug. 1964 - C.S. File 53/40-87

-----  
Found original BTs as follows:  
12" now 11" Laurel N.40°E., 23.1 ft., face rotted, never healed over, now snag.  
14" now 15" Laurel S.10°E., 10.6 ft., shows faint scribe.  
14" now 16" Laurel S.60°W., 37.0 ft., shows faint scar.  
40" now 48" D.Fir N.65°W., 21.8 ft., recorded as Laurel, shows good scars.

Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 7 W  
S 10 | S 11  
S 15 | S 14  
1964

New Bearing trees:  
6" W.Fir N.45°E., 10.4 ft. mkd. T30S R7W S11 CS BT.  
9" D.Fir S.35°E., 9.5 ft. previously scribed "T30S R7W S14 BT".  
16" Laurel S.60°W., 37.0 ft. mkd. T30S R7W S15 CS BT. (Orig. BT.)  
8" W.Fir N.27°W., 27.4 ft. mkd. T30S R7W S10 CS BT.  
Also there is a 39" Cedar N.13°E., 38.0 ft. bark scribed previously, mkd. S11 T30S R7W BT.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #571, surveyed May/June 1965 - (DCSO records Vol. 33 Page(s) 13862)

-----  
The Sec. cor., perpetuated by the County in 1964, monumented with an iron post, 1" dia., firmly set, extending 12" above the ground with properly mkd. brass cap, from which the original bearing trees:  
A Madrone snag 10" dia., bears N.44½°E., 37 lks. dist. with rotted blaze. (Rec. N.40°E., 33 lks.)  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A down Madrone 15" dia., bears S.10°E., 16 lks. dist. with scribe marks S7W visible on rotted blaze.  
A Madrone 14" dia., bears S.66°W., 56 lks. dist. remarked T30S R7W S15 CS BT on double blaze, by the County. (Rec. S.60°W.)  
A Fir 48" dia., bears N.65°W., 29 lks. dist. with partially opened blaze. (Rec. a Madrone 33 lks.)  
and County Surveyor's bearing trees:  
A W.Fir 6" dia., bears N.45°E., 16 lks. dist. mkd. T30S R7W S11 CS BT on double blaze.  
A W.Fir 8" dia., bears N.27°W., 41 lks. dist. mkd. T30S R7W S10 CS BT on double blaze.  
and bearing trees of which I have no record:  
A Cedar 40" dia., bears N.15°E., 56½ lks. dist. mkd. S11 T30S R7W BT on bark blaze.  
A Fir 9" dia., bears S.35°E., 14 lks. dist. with fragmentary scribe marks visible on partially healed double blaze.  
Add marks BLM 1965 to brass cap.

BLM resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson, Cadastral Surveyors - under Group #1456, surveyed Sept. 1988/Feb. 1989 - (DCSO records Vol. 50 Page(s) 19032-33)

-----  
The cor. of secs. 10, 11, 14 and 15, monumented with an iron post 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with properly mkd. brass cap from which the remains of the original bearing trees  
A madrone stump, size indeterminate, bears S. 10° E., 16 lks. dist., no marks visible.  
A sawed fir stump, 50 ins. diam., bears N. 65° W., 29 lks. dist., with healed blaze.  
and the remains of a bearing tree mkd. by Vernon R. Tracy, Deputy County surveyor, in 1964  
A grand fir snag, 9 ins. diam., bears N. 45° E., 16 lks. dist., with scribe marks 30S R7W S11 CS BT visible on open blaze.  
and the remains of bearing trees recorded by Jelley in 1965  
A cedar, 42 ins. diam., bears N. 15° E., 56½ lks. dist., with scribe marks S11 T30S R7 visible on bark blaze.  
A fir snag, 9 ins. diam., bears S. 35° E., 14 lks. dist., with healed double blaze.  
and new bearing trees  
A grand fir, 4 ins. diam., bears S. 43° E., 66 lks. dist., mkd. X BT.

(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A grand fir, 8 ins. diam., bears S. 37° W., 100 lks. dist., mkd. T30S R7W S15 BT.

A grand fir, 11 ins. diam., bears N. 16°W., 52 lks. dist., mkd. T30S R7W S10 BT.

The corner is located North, 1.00 chs. dist. form a gravelled road, 25 lks. wide, bears E. and W.

From this point, United States Coast and Geodetic Survey triangulation station "BUCK MOUNTAIN," bears N. 78° 14' 00" W., 83.202 chs. dist., monumented with a brass tablet, 3½ ins. diam., firmly set flush with bedrock, mkd. BUCK MTN 1942 and a triangle.