

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7242)

Set ¼ sec. post, from which
A Laurel 8" dia., bears East, 10 lks. dist.
A Fir 8" dia., bears N.85°W., 11 lks. dist.

Cor. Fd. OK, by W.H. Byars, under Contract #450, dated July 28, 1882 - (DCSO records, Vol. 17 Pg. 7258)

Douglas County Surveyors Office - Vernon R. Tracy; Mike Darby; Jack Barnett, crew - Aug. 1964 - C.S. File 53/40-92

Found - 8" now 18" D.Fir N.85°W., 7.3 ft., Open and find "¼" scribe.

No trace of Laurel to East.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 7 W
¼ S10 | S11
1964

New BTs -14" D.Fir S.75°W., 20.0 ft. mkd. ¼ S10 CS BT.
32" D.Fir S.66°E., 31.8 ft. mkd. ¼ S11 CS BT.

This corner lies approx. 100 ft. over top of ridge on N. slope.

Fd. and Used in BLM resurvey by Rogers; Bedell; Peterson, Cadastral Surveyors under Group # 1456, surveyed Sept. 1988/Feb. 1989 - (DCSO records, Vol. 50 Page 19033)