

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7242)

-----  
Set post cor. to secs. 2, 3, 10 and 11, from which  
A Willow 6" dia., bears N.55°E., 10 lks. dist.  
A Fir 30" dia., bears S.70°E., 11 lks. dist.  
A Laurel 8" dia., bears S.58°W., 59 lks. dist.  
A Fir 30" dia., bears N.64°W., 19 lks. dist.

Cor. Fd. and used in GLO resurvey by Byars, under Contract #450, dated July 28, 1882 - (DCSO records, Vol. 17 Pages 7258; 7259-60)

Douglas County Surveyors Office - Vernon R. Tracy, Mike Darby and Jack Barnett, crew - Sept. 1964 - C.S. File 53/40-93

-----  
Found - 30" now 36" D.Fir snag, N.64°W., 12.5 ft., open and find "BT" scribe.  
30" now 38" D.Fir, alive, S.70°E., 7.3 ft., shows good "S", bark scribe.  
No trace of Laurel or Willow BTs.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 7 W  
S 3 | S 2  
S 10 | S 11  
1964

New BTs -25" W.Fir N.14°W., 38.8 ft. mkd. T30S R7W S3 CS BT.  
15" W.Fir N.3°E., 80.6 ft. mkd. T30S R7W S2 CS BT.  
38" D.Fir S.70°E., 8.0 ft. mkd. T30S R7W S11 CS BT.  
(Orig. BT.)  
6" Laurel S.27°W., 43.2 ft. mkd. S10 CS BT.

Fd. OK, Oct. 1980 by H. Johnstone - M 86-3 and Jan. 1981 - M 86-77