

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7243)

Set ¼ sec. post, from which
A Fir 10" dia., bears N.12°E., 31 lks. dist.
A Fir 10" dia., bears S.25°W., 36 lks. dist.

Fd. and used corner in GLO resurvey by Byars, under Contract #450, dated July 28, 1882 - (DCSO records, Vol. 17 Pg. 7258)

Douglas County Surveyors Office - John M. Powell, Frank Jones, and Terry Connell, crew - July 11, 1966 - C.S. File 53/40-84

Found - 10" D.Fir now 18", N.12°E., 20.5 ft. Tree had been opened for scribe "S". Opened more for /4.
No trace of SW. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 7 W
¼ S3 | S2
1966

New BTs -21" D.Fir S.17°E., 47.0 ft. scribed ¼ S2 CS BT.
No other good trees handy in sec. 3, so reblazed and rescribed 18" D.Fir N.12°E., 20.5 ft. scribed ¼ S2 CS BT.

This corner lies at bottom of 15.0 ft. rock bluff on very steep, West slope about 75 ft. East of spring branch.