

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7239)

Set ¼ sec. post, from which
A Pine 8" dia., bears S.52°E., 50 lks. dist.
A Fir 5" dia., bears N.70°W., 10 lks. dist.

Not fd by DCSO 6/1965 C.S. File 53/40-76

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #897, surveyed Sept. 1976/June 1977 - (DCSO records Vol. 41 Page(s) 16248)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 30 S R 7 W
¼ $\frac{S 26}{S 35}$
1977

from which
A Fir 12" dia., bears N.4½°E., 28½ lks. dist. mkd. ¼ S26 BT.
A Fir 7" dia., bears S.65 3/4°E., 103½ lks. dist. mkd. ¼ S35 BT.