

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7242)

-----  
Set ¼ sec. post, from which  
A Laurel 5" dia., bears S.10°W., 62 lks. dist.  
A Laurel 6" dia., bears N.65°W., 80 lks. dist.

W. F. Briggs - March 24, 1892 - Field Book 4 Page 57

-----  
Red Fir 5" dia. for corner marked ¼ S. C.S., from which  
A Fir 5" dia., bears S.5°W., 5 lks.  
A Fir 4" dia., bears North, 7 lks.  
The original BTs could not be found.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Barnett; Mike Darby, crew - Aug. 1964 - C.S. File 53/40-89

-----  
Found - 5" R.Fir corner tree, now 16", shows very faint scar, has been used as fence corner. (Briggs 1892)  
4" D.Fir now 7" stump, North, 4.6 ft., cut open and found scribe.  
5" D.Fir now 16" snag S.5°W., 3.3 ft., cut open and found "B" scribe. Fell snag to prevent possible damage to corner.

Set Brass cap Witness corner mkd. County Surveyors Office  
T 30 S R 7 W  
W.C. 4 ft. E.  
¼ S 11  
S 14  
1964

This monument is 4.0 ft. West of corner tree.  
New BTs -20" D.Fir N.51°E., 14.2 ft. mkd. W.C. ¼ S11 CS BT.  
22" D.Fir S.15°W., 15.7 ft.

BLM resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson, Cadastral Surveyors - under Group #1456, surveyed Sept. 1988/Feb. 1989 - (DCSO records Vol. 50 Page(s) 19031-32)

-----  
The ¼ sec. cor. of secs. 11 and 14, reestablished and recorded by Briggs, Deputy County Surveyor, in 1892, and further perpetuated and recorded by Tracy, Deputy County Surveyor, in 1964, and is accepted as the corner; monumented with the remains of the corner tree mkd. by Briggs, a fir snag, 16 ins. diam., with healed blaze on S. face, from which new bearing trees: (Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 4 ins. diam., bears S. 39° E., 111 lks. dist., mkd.  
X BT  
A cedar, 17 ins. diam., bears N. 26° W., 74 lks. dist.,  
mkd. ¼ S11 BT.

From this point, a witness corner established by Vernon R. Tracy, Deputy County Surveyor, in 1964, bears N. 80° W., 0.06 chs. dist., monumented with an iron post, 1¼" diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T30S WC 4 FT E ¼ S11 S14 R7W 1964, from which the remains of a bearing tree mkd. by Tracy:

A fir stump, 22 ins. diam., bears N. 50° E., 21 lks. dist., with healed blaze.