

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 600120

PRIMARY CORNER DESCRIPTION S 1/16 Corner for Sec 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM survey by James E. Jelley, Cadastral Surveyor - under Group #897, surveyed Sept. 1976/June 1977 - (DCSO records Vol. 41 Page(s) 16249)

Point for the S 1/16 cor. of secs. 35 & 36
Set an iron Post 28" long, 2½" diam. Flush with the surface of the ground. Brass cap marked,
S 1/16
S 35|S 36
1977
A pine, 7" dia., bears S.87¾°E. 113½ lks. Mkd S 1/16 S.36 BT
A basalt boulder, 5x5x3 ft above ground bears S.26¾°W., 31 lks mkd X B0 on top.

Mark Smalley, Roseburg Resources - 1992 - M112-52

Found - 1977 cadastral BCIP
5'x5'x3' boulder S.26¾°E., 20.5' mkd: "X B0"
7" Pine S.87¾°E., 74.91' rotten
Scribed- 17" Fir S.26°E., 55.8' "S 1/16 S36 BT"

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 4/2/2025 - C.S. File 67/60-20

Found - 1977 BLM brass cap buried 15"
5'x5'x3' boulder S.26¾°W. 20.5 ft marked X B0
27" fir S.26°E. 55.3 ft (Rec 55.8 ft)
New - Add 3½" mag nail right side center.
Compass decl. 14½°E.
O CRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N 30648.630 E 122887.456