

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7233)

-----  
Set ¼ sec. post, from which  
A B.Oak 14" dia., bears N.70°E., 46 lks.  
A W.Oak 14" dia., bears N.85°W., 48 lks.

Survey by John H. Markham, Jr. - Wit: M.J. Guse - For: M.J. Guse - Nov. 7, 1953 - C.S. File 41/254-3

-----  
Determined by original bearing trees:  
A 16" W.Oak bears N.85°W., 15.5 ft.  
A 14" B.Oak windfall, bears N.70°E., 40.0 ft.  
At corner point, Set 1" x 30" Iron pipe, from which  
A 14" Laurel bears S.43°E., 46.5 ft. mkd. ¼ S36 BT.  
A 6" W.Oak bears N.67°30'W., 33.3 ft. mkd. ¼ S BT.  
S.P.R.R. mile post #536.53 bears S.36°W., 188 ft. dist.

Douglas Co. Surveyors Office - Vernon R. Tracy; Mike Darby; Jack Barnett, crew - Nov. 13, 1964 - C.S. File 53/40-61

-----  
Found - One orig. BT standing and hole in ground where other BT was.  
Markham's corner, obliterated.  
14" now 20" W.Oak N.85°W., 31.7 ft., find "/L" reverse scribing.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 7 W  
¼ S35|S36  
1964  
New BTs -8" W.Oak S.23°E., 21.8 ft. mkd. ¼ S36 CS BT.  
9" W.Oak S.62°W., 17.5 ft. mkd. ¼ S35 CS BT.

Cor. Fd. and used in BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #897, surveyed Sept.1976/June 1977 - (DCSO records Vol. 41 Page(s) 16243)

Survey by Mark Smalley, LS #2534 - For: Roseburg Resources - May/July 1992 - M 112-52

-----  
Found - 1964 DCSO brass cap with iron pipe, properly mkd.  
8" Oak bears S.21 ¾°E., 21.8 ft., healed face.  
14" Oak bears N.85°W., 31.7 ft., down.  
6" Oak bears N.67½°W., 33.3 ft., stump.  
9" Oak bears S.62 ¾°W., 17.2 ft., stump.  
New BT - 7" Oak bears N.23°W., 12.7 ft. scribed ¼ S35 BT.