

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7233)

-----  
Set post cor. to secs. 25, 26, 35 and 36, from which  
A Live Oak 4" dia., bears N.25°E., 11 lks. dist.  
A Live Oak 4" dia., bears S.60°E., 14 lks. dist.  
A Fir 30" dia., bears S.60°W., 78 lks. dist.  
A Fir 24" dia., bears N.80°W., 72 lks. dist.

Survey by A.R. Evans - Wit: G.E. Johnson and Merle Evans - For: S.P. Davis - Aug. 15, 1953 - C.S. File 41/253-1 and C.S. File 41/259

-----  
Reset from original BTs - Fir, NW. and Fir stump, SW. Old corner post.  
Set 4" x 4" x 48" Fir post, from which  
8" Live Oak N.20°E., 10.3 ft. mkd. T30S R7W S25 RE 2741 BT  
6" Live Oak S.68½°E., 11.8 ft. mkd. T30S R7W S36.  
6" Live Oak S.11½°W., 16.4 ft. mkd. T30S R7 S35.

Survey by John H. Markham, Jr. - Wit: M.J. Guse - For: M.J. Guse - Nov. 7, 1953 - C.S. File 41/254-2

-----  
A 30" Fir stump bears S.67°W., 51.0 ft. (O.B.T.)  
40" Fir bears N.74°W., 47.5 ft.  
Live Oak stump bears N.27°E., 8.8 ft.  
Live Oak stump bears S.63°E., 9.0 ft.  
At corner point, found large pile of stones and scribed post, from which  
A 6" Live Oak bears S.60°W., 11.1 ft. mkd. T30S R7W S36 BT  
A 9" Live Oak bears N.24°E., 9.7 ft. mkd. T30S R7W S25 BT  
A 6" Live Oak bears S.3°W., 16.0 ft. mkd. T30S R7W S35 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman crew - Feb. 1964 - C.S. File 53/40-52

-----  
Found mound of stone and all BTs as recorded except 6" Live Oak bears S.3°W., 16.4 ft. not S.11½°W., 16.4 ft.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 7 W  
S 26 | S 25  
S 35 | S 36  
1964

(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by James E. Jelley and Charles E. Akin, Jr., Cadastral Surveyors, under Group #'s 734 & 829, surveyed April 1971/oct. 1973 (DCSO records Vol. 37 Page(s) 15145-46)

-----  
The sec. cor., perpetuated and recorded by Evans in 1953, and subsequently perpetuated by Byron in 1964, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, and in a mound of stone, 2 ft. base, 1 ft. high, with 1964 brass cap, from which the only remaining original bearing tree

A Fir 34" dia., bears N.76°W., 72 lks. dist. with healed blaze. (Rec. N.80°W.)

and bearing trees mkd. by Evans

An Oak 10" dia., bears N.21°E., 15 lks. dist. with scribe marks T30S R7W S25 BT visible on open blaze.

An Oak 9" dia., bears S.64°E., 18 lks. dist. with scribe marks R7W S36 bT visible on partially open blaze.

An Oak 8" dia., bears S.2°E., 25 lks. dist. with scribe marks T30S R7W S35 visible on partially open blaze.

and a new bearing tree

An Oak 10" dia., bears S.11½°W., 35 lks. dist. mkd. T30S R7W S35 BT.

Cor. Fd. and used in BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #897, surveyed Sept. 1976/June 1977 - (DCSO Records, Vol. 41 Pg. 16244)

Fd. OK July 1992 by Mark Smalley - M 112-52