

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7234)

Set ¼ sec. post, from which
A Pine 6" dia., bears N.40°E., 70 lks. dist.
A Pine 6" dia., bears N.55°W., 77 lks. dist.

BLM resurvey by James E. Jelley and Charles E. Akin, Jr., Cadastral Surveyors, under Group #'s 734 and 829, surveyed April 1971/Oct. 1973 - (DCSO records Vol. 37 Page(s) 15146-47)

The ¼ sec. cor., determined at record bearing and distance from the remains of the original bearing tree:

A Pine stump 24" dia., bears N.55°W., 77 lks. dist. with fragmentary scribe marks visible on partially opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, and in a mound of stone, 3 ft. base, to top. with brass cap

mkd:
1/4
S 26 S 25
T 30 S R 7 W
1971

from which new bearing trees:

A Pine 16" dia., bears S.25°E., 63 lks. dist., mkd. ¼ S25 BT.
A Pine 18" dia., bears S.47¼°W., 94 lks. dist. mkd. ¼ S26 BT.