

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7234)

-
- Set post cor. to secs. 23, 24, 25 and 26, from which
- A Fir 12" dia., bears N.5°E., 54 lks. dist.
 - A Fir 8" dia., bears S.68°E., 53 lks. dist.
 - A Fir 5" dia., bears S.30°W., 9 lks. dist.
 - A Cedar 14" dia., bears N.1°W., 42 lks. dist.

Survey by John H. Markham, Jr. - Wit: J.H. Brown - may 10, 1951 - C.S. File 40/311

-
- Determined by original bearing trees (found scribe on all BTs)
- A Cedar 30" dia., bears N.1°W., 26.0 ft.
 - A Fir 26" dia., bears N.13°E., 35.0 ft.
 - A Fir snag bears S.65°E., 35.0 ft.
- At corner point, Set 1" x 30" Iron pipe, from which
- A Fir 10" dia., bears S.45°E., 13.0 ft. mkd. S25 BT.
 - A W.Fir 33" dia., bears S.32°W., 6.0 ft. mkd. S26 BT.

BLM resurvey by James E. Jelley and Charles E. Akin, Jr., cadastral surveyors, under Group #'s 734 and 829, surveyed April 1971/Oct. 1973 - (DCSO records Vol. 37 Page(s) 15147-48)

The Sec. Cor., perpetuated and recorded by Markham in 1951, monumented with an iron pipe, 1" dia., firmly set, projecting 4" above ground, from which the remains of the original bearing trees:

- A Fir 26" dia., bears N.12½°E., 54 lks. dist. with healed blaze. (Rec. N.5°E.)
 - A Fir snag 35" dia., bears S.65°E., 53 lks. dist. with healed blaze. (Rec. S.68°E.)
 - A root hole bears S.30°W., 9 lks. dist. with a down Fir alongside, 33" dia., with healed blaze.
 - A Cedar 35" dia., bears N.1°W., 42 lks. dist. with healed blaze.
- and a bearing tree mkd. by Markham:
- A root hole bears S.45°E., 20 lks. dist. with a down Fir alongside, 11" dia., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 30 S R 7 W
S 23 S 24
S 26 S 25

1971 (Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new bearing trees:

A Fir 15" dia., bears S.31½°E., 76½ lks. dist. mkd. T30S
R7W S25 BT.

A W.Fir 8" dia., bears S.5°W., 73½ lks. dist. mkd. T30S
R7W S26 BT.

A W.Fir 10" dia., bears N.15 3/4°W., 44 lks. dist. mkd.
T30S R7W S23 BT.

Deposit the iron pipe alongside the iron post.

BLM Field corrections report filed March 11, 1982 in C.S.
File 61/33-1

"This cap moved N.059 chs. and W.207 chs. to correct
position. It appears that the corner was moved during
logging operation."