

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7235)

-----

Set post cor. to secs. 13, 14, 23 and 24, from which

- A Fir 48" dia., bears N.65°E., 41 lks. dist.
- A Fir 60" dia., bears S.80°E., 21 lks. dist.
- A Laurel 24" dia., bears S.48°W., 75 lks. dist.
- A Fir 12" dia., bears N.50°W., 38 lks. dist.

Survey by John H. Markham, Jr. - Wit: Geo. Vaughn and J.H. Brown - May 19, 1951 - C.S. File 40/311

-----

Determined by original bearing trees

- A Fir 70" dia., bears S.80°E., 14.0 ft., bark scribed S24 T30S R7W BT.
- A Laurel 30" dia., bears S.48°W., 50.0 ft.

At corner point, Set wood stake, from which

- A Laurel 30" dia., bears N.67°W., 42.5 ft. mkd. S14 BT.
- A Laurel 40" dia., bears N.2°W., 38.0 ft. mkd. S13 2880 BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Terry Connell, crew - July 11, 1966 - C.S. File 53/40-85

-----

Found - 70" D.Fir, down, S.80°E., 14.0 ft. bark scribe visible. (Original BT)

- 30" Laurel snag, S.48°W., 50.0 ft., faint scribe visible. (orig. BT)
- 30" Laurel now 34" N.67°W., 42.5 ft, shows good scar.
- 40" Laurel now 42" N.2°W., 38.0 ft. shows scar.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 7 W
<u>S 14</u>   <u>S 13</u>
S 23   S 24
1966

New BTs -7" D.Fir S.54°W., 30.1 ft. scribed T30S R7W S23 CSBT

- 11" D.Fir S.37½°E. 39.8 ft scribed T30S R7W S24 CSBT
- 9" D.Fir N.74°E., 38.0 ft. scribed T30S R7W S13 CSBT

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2191, Surveyed April/May 2008 - (DCSO records Vol. 56 Page(s) 22134-5)

-----

The cor. of secs. 13, 14, 23, & 24, perpetuated by Markham, in 1951, subsequently perpetuated by the Douglas Co Surveyors Office in 1966, determined at record bearing & dist. from the remains of the orig. BTs

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A roothole, bears S.80°E., 18.5 ft.. (Record, 13.9 ft.)  
 A decayed madrone stump, size indeterminate, bears S.48°W., 49.5 ft., with no marks visible.  
 and the remains of bearing trees mkd. by Markham  
 A decayed madrone stump, size indeterminate, bears N.1½°E., 36.4 ft., with no marks visible.  
 A roothole, bears N.70°W., 48.1 ft.  
 and the remains of BTs mkd by the Douglas Co Surveyors Office  
 A roothole, bears S.35½°E., 38.8 ft., alongside of which is a down, decayed fir snag, 10" dia., with fragmentary scribe marks visible on a partially healed blaze.  
 At the cor. point  
 Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd.

T30S	R7W
S 14	S 13
S 23	S 24
2008	

from which new bearing trees  
 A fir, 15" dia., bears N.75¼°E., 9.9 ft., mkd. T30S R7W S13 BT.  
 A fir, 10" dia., bears S.7¾°E., 15.9 ft., mkd. T30S R7W S24 BT.  
 A fir, 11" dia., bears S.27½°W., 18.6 ft., mkd. T30S R7W S23 BT.  
 A fir, 6" dia., bears N.18°W., 14.1 ft., mkd. T30S R7W S14 BT.  
 Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.  
 Deposit a magnet in a white plastic case at the base of the stainless steel post.  
 An iron post, 29" long, 1¼" dia., with brass cap mkd. COUNTY SURVEYORS OFFICE T30S R7W S14 S13 S23 S24 1966, was found disturbed and lying loose, and was placed inside the stainless steel post.

Brent Knapp - For: Roseburg Resources Co. - 8/2023 - M182-53  
 -----  
 Found - 2008 BLM brass cap  
 Metal "L" post; North 1.0'  
 Roothole, S.80°E., 18.5'  
 Roothole, S.48°W., 49.5'  
 Decayed Madrone stump (no markings) N.1°E., 36.4'  
 12" Pine, Lone Rock tag (unrecorded) N.59°W., 3.8'  
 16" Fir, healed scar & tag; N.75¼°E., 9.9'  
 11" Fir, healed scar & tag; S.7¾°E., 15.9'  
 12" Fir, healed scar & tag; S.27½°W., 18.6'  
 8" Fir, healed scar & tag; N.18°W., 14.1'