

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7236)

-----  
Set post cor. to secs. 11, 12, 13 and 14, from which  
A Pine 36" dia., bears N.85°E., 98 lks. dist.  
A W.Oak 24" dia., bears S.65°E., 211 lks. dist.  
A Pine 48" dia., bears S.70°W., 14 lks. dist.  
A W.Oak 8" dia., bears N.62°W., 84 lks. dist.

Douglas Co. Surveyors Office - Vernon R. Tracy, Mike Darby and Jack Barnett, crew - Aug/Sept. 1964 - C.S. File 53/40-88

-----  
Found - 48" now 42" Pine snag S.70°W., 9.2 ft., shows good scribe. (Orig. BT)  
36" now 48" Pine, down, N.85°E., 64.7 ft., shows scribe. (Orig. BT)  
Both Oaks gone.

Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 7 W  
S 11 | S 12  
S 14 | S 13  
1964

New BTs -7" D.Fir S.15°W., 6.9 ft. mkd. T30S R7W S14 CSBT  
12" D.Fir S.21°E., 16.8 ft. mkd. T30S R7W S13 CSBT  
7" D.Fir N.87°E., 20.8 ft. mkd. T30S R7W S12 CSBT  
No tree close in sec. 11.  
Fence corner bears S.31°E., 5.0 ft. with fence going S. & E.

BLM resurvey by James E. Jelley and Charles E. Akin, Jr., cadastral surveyors, under Group #'s 734 and 829, surveyed April 1971/Oct. 1973 - (DCSO records Vol. 37 Page(s) 15150)

-----  
The sec. cor. perpetuated and recorded by Tracy, 1964, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with 1964 brass cap from which the remains of the original bearing tree  
A burned Pine snag, 42" dia., bears S.70°W., 14 lks. dist. with burned blaze.  
and bearing trees mkd. by Tracy  
A burned Fir 8" dia., bears N.87°E., 31 lks. dist. with burned double blaze.  
A burned Fir 8" dia., bears S.15°W., 10 lks. dist. with a burned double blaze.  
A burned Fir 13" dia., bears S.21°E., 25 lks. dist. with burned double blaze.  
and a new bearing tree  
(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A burned Fir 15" dia., bears N.2°E., 17 lks. dist. mkd.  
T30S R7W S12 BT.  
No other trees available within limits.

Douglas Co. Surveyors Office - Gary L. Langlitz, Peter Earle,  
crew - Feb. 27, 1974 - C.S. File 56/43-22

-----  
Found - 1964 DCSO brass cap. At this time, I find no  
indication on the monument as to its range  
designation. I now mark the monument with a 7 to  
read "R7W".

7" D.Fir, burnt and dead, bears S.15°W., 6.9 ft.  
scribing has been chopped out.

12" D.Fir, burnt and dead, bears S.21°E., 16.8 ft.  
scribing grown over.

7" D.Fir, burnt and dead, bears N.87°E., 20.8 ft.,  
face burnt out.

The 2 original Pine BTs mentioned in the 1964 visit  
are now badly burnt.

A new BT, apparently marked by BLM cadastral survey  
crew, an 18" D.Fir, burnt and dead, bears  
N.02°E., 11.2 ft. to face of blaze, scribed "T30S  
R7W S12 BT". This tree has been marked since the  
area burned, tag dated 10-73.

As there are no living trees in the vicinity, I set a steel  
fence post with survey marker warning sign attached 1.0 ft.  
North of corner point.

BLM resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W.  
Peterson, Cadastral Surveyors - under Group #1456, surveyed  
Sept. 1988/Feb. 1989 - (DCSO records Vol. 50 Page(s) 19030-  
31)

-----  
From the cor. of secs. 11, 12, 13, and 14, monumented with an  
iron post, 1¼ ins. diam., firmly set, projecting 10 ins.  
above ground, with a properly mkd. 1964 brass cap mkd.  
from which the remains of an original bearing tree

A burned pine snag, 28 ins. diam., bears S. 70° W., 14  
lks. dist., with burned blaze.

and the remains of bearing trees mkd. by Tracy in 1964

A burned fir snag, 8 ins. diam., bears N. 87° E., 31 lks.  
dist., with burned double blaze.

A burned fir stump, 12 ins. diam., bears S. 21° E., 25  
lks. dist., with burned blaze.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A root hole, bears S. 15° W., 10 lks. dist., with a down burned fir alongside, 7 ins. diam., with burned double blaze.  
and the remains of a bearing tree mkd. by Jelley and Akin  
A burned fir snag, 16 ins. diam. bears N. 2° E., 17 lks. dist., with scribe marks T30S R7W S12 BT visible on open blaze.  
and new bearing trees  
A pine, 4 ins. diam., bears N. 78° E., 38½ lks. dist., mkd. X BT on bark.  
A madrone, 6 ins. diam., bears S. 88° W., 33 lks. dist., mkd. T30S R7W S14 BT on bark.  
A madrone, 4 ins. diam., bears N. 6° W., 37 lks. dist., mkd. X BT on bark.  
A steel fence post, 5 ft. high, is alongside the iron post.

Fd. OK Feb. 1995 - M 121-59

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2191, Surveyed April/May 2008 - (DCSO records Vol. 56 Page(s) 22136-8)

-----  
The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.  
from which the remains of an original bearing tree  
A roothole, bears S.70°W., 9.2 ft., alongside of which is a burnt pine snag, size indeterminate, with no marks visible on a burnt, weathered blaze.  
and the remains of BTs mkd. by the Douglas County Surveyors Office in 1964, reported by Rogers, Bedell, and Peterson  
A sawed fir stump, 8" dia., bears N.87°E. 20.5 ft. with no marks visible on burnt, partially healed double blaze.  
A sawed, decayed fir stump, 15" dia., bears S.21°E., 16.5 ft., with no marks visible.  
A decayed fir stump, size indeterminate, bears S.15°W., 6.6 ft., with no marks visible.  
and the remains of a BT mkd. by Jelley and Akin, reported by Rogers, Bedell, and Peterson  
A fir stump, size indeterminate, bears N.2°E., 11.2 ft., alongside of which is a burnt, decayed down fir, size indeterminate, with no marks visible.  
and the remains of BTs mkd. by Rogers, Bedell, and Peterson  
A pine, 12" dia., bears N.74°E., 25.4 ft., with no marks visible on a burnt, partially healed blaze. (Record, N.78°E.)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A madrone stump, 4" dia., bears N.10°W., 24.4 ft., alongside of which is a down madrone, 4" dia., with scribe marks X BT visible on an open, weathered double blaze. (Record, N.6°W.)  
and new bearing trees  
A pine, 6" dia., bears S.25¾°E., 19.2 ft., mkd. T30S R7W S13 BT.  
A fir, 4" dia., bears S.50°W., 19.9 ft., mkd. X BT.  
A cedar, 5" dia., bears N.54°W., 24.9 ft., mkd. T30S R7W S11 BT.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.