

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7237)

-----

Set post cor. to secs. 1, 2, 11 and 12, from which

- A W.Oak 6" dia., bears N.20°E., 54 lks. dist.
- A Pine 60" dia., bears S.70°E., 96 lks. dist.
- A W.Oak 12" dia., bears S.55°W., 263 lks. dist.
- A W.Oak 8" dia., bears N.10°W., 175 lks. dist.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - April/Sept. 1956 - C.S. File 42/192-4

-----

Found a 72" Pine bears S.70°E., 63.4 ft. Orig. BT.  
 At corner point, Set large truck axle with flange up, from which

- 12" Cedar bears N.20°W., 5.7 ft. mkd. S2 BT.
- 12" Cedar bears N.80°W., 7.8 ft. mkd. S11 BT.
- 5" W.Oak bears N.72°E., 34.0 ft. mkd. S1 BT.
- 12" Cedar bears S.52°E., 11.8 ft. mkd. S12 BT.

Road bears South, 53.0 ft. Fence runs N.55°E. and S.55°W. through corner.

Douglas Co. Surveyors Office - R.B. Kimberling; P.L. Earle; F.C. Silagy, crew - April 4, 1978 - C.S. File 59/46-45

-----

Found - A 1½" x 35" axle with 5" flange down, spline end 15" above ground.

- A 52" P.Pine bears S.70°E., 63.4 ft. with visible scribing "S2" in a chopped open blaze.
- The East fork of a 12" I.Cedar is now 16" and bears N.20°W., 5.7 ft. with scribing "S2 BT" in a partly healed double blaze.
- A 12" now 16" I.Cedar bears N.80°W., 7.8 ft. with a partly healed double blaze.
- A 5" now 8" W.Oak bears N.74°E., (Rec. N.72°E.) 34.0 ft. with a well healed double blaze.
- A 12" now 13" I.Cedar bears S.52°E., 11.8 ft. with visible scribing "S12 BT" in a partly healed double blaze. Scribing is written up the trees.

Set a 1" x 36" I.P. with brass cap 6" above ground at axle location marked: Douglas County Surveyor

T 30 S R 7 W  
 S 2 | S 1  
 S 11 | S 12  
 1978

(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

I set axle S.W., 0.3 ft. from the brass cap with the spline end 1.0 ft. above ground.  
New BT - A 12" I.Cedar bears S.52°W., 11.7 ft. I double blaze and scribed "T30S R7W S11 CS BT"  
Remains of a fence )NE-SW) are at the NW. BLM bearing tree.

Cor. Fd. and used in BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1007, surveyed Aug. 1980/March 1982 - (DCSO records, Vol. 43 Pgs. 16789-90)

Cor. Fd. and used BLM resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson, Cadastral Surveyors - under Group #1456, surveyed Sept. 1988/Feb. 1989 - (DCSO records Vol. 50 Page(s) 19029-30)