

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7238)

Set ¼ sec. post, from which
A Pine 12" dia., bears N.48°E., 283 lks. dist.
An Alder 8" dia., bears S.50°W., 254 lks. dist.

Not Fd, DCSO 3/1965 - C.S. File 53/40-62

Survey by Bruce Rogers - For: Strout Realty - Jan. 1974 - M 49-53

Found - 5/8" Iron rod, S.12½°W., 44.6 ft. (Not of record)
A blazed 12" Alder mkd. with blue keel "26", bears N.24°E., 27.4 ft.
A blazed 16" Alder markings unreadable, bears S.60°W., 87.5 ft.
Set 5/8" Iron rod by single proportion.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1007, surveyed Aug. 1980/March 1982 - (DCSO records Vol. 43 Page(s) 16790)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 30 S R 7 W
1/4
S 2 | S 1
1980

from which
An Alder 26" dia., bears N.25°E., 39 lks. dist. mkd. ¼ S1 BT on bark.
A Madrone 16" dia., bears S.61°W., 320 lks. dist. mkd. ¼ S2 BT on bark.

Fd. and used in BLM survey by Dale T. Bedell, Cadastral Surveyor, under Group #1660, surveyed April/June 1993 - (DCSO records, Vol. 51 Pg. 19366)