

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. cor for 1, 2 & 35, 36 of T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey - W.H. Byars - contract #152 dated Jun 3, 1871
(DCSO records Vol. 17 Pg. 7231)

Set post from which:

- A Laurel, 30" diam., bears N.22°E., 24 lks.
- A Laurel, 24" diam., bears S.68°E., 42 lks.
- A Laurel, 30" diam., bears S.70°W., 34 lks.
- A laurel, 20" diam., bears N.85°W., 42 lks.

Retracement - Roy T. Campbell, Dep. Surveyor - contract # 789
- Aug 1909 (DCSO Vol. 15 Page 6554)

At the cor. of 1, 2, 35, & 36, which is a post badly decayed,
but marked and witnessed as described by the surveyor
general; in place of the post I set a diorite stone, 15x8x6",
10" in the ground, mkd. with 1 notch on E. and 5 notches on
W. edge

John H. Markham Jr. - for Stomar Lumber Co. - Apr/Sep 1956 -
C.S. 42/192-2

Point for corner determined by OBT

- A 24" La., bears S.68°E., 27.7 ft - Fd. scribe.
- At corner point set 3/4"x30" iron pipe from which:
- A 18" La., bears S.86°W., 34 ft., mkd. S2, T30-7, BT
 - A 30" La., bears N.21°W., 35 ft., mkd. S35, T29-7, BT
 - A 15" La., bears N.39°E., 36 ft., mkd. S36 T29-7, BT
 - A 35" La., bears S.24°E., 45 ft., mkd. S1 T30-7, WM., BT

R.B. Kimberling, P.L Earle - April 5, 1978 - Do. Co. Surveyor
Office - C.S. 59/46-44

- Found - A 3/4" I.P. 12" above ground, bears S.58°W., 2 ft.
from corner, with a 3"x3" squared post at the W.
side.
- An OBT, a 24" madrone (laurel) bears S.68°E., 27.7
ft., with an opened blaze and visible scribing
"S-T30S R7"
 - A 18" now 24" madrone (laurel) bears S.83½°W., 35.7
ft. (Rec. S.86°W., 34.0 ft) with visible scribing
"T30S R7" in a double partly healed blaze.
 - A 30" now 31" Madrone, bears N.21°W., 35.0 ft., with
visible scribing "3-29" in a double partly healed
blaze
 - A 15" now 18" Madrone, bears N.39°E., 34.0 ft. (Rec.
36.0 ft) with visible scribing "3-29-R7-BT" in a
double partly healed blaze.

(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec cor for 1, 2 & 35, 36, of T29-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A 35" now 39" Madrone bears S.20½°E., (Rec. S24°E.)
45.0 ft., with visible scribing "S1 T30S R7W"
in a double partly healed blaze.
Note: Scribing is cut horizontal in all blazes.
Set - A 1"x36" I.P. with brass cap set 6" above ground and
mkd: Douglas County Surveyor 1978
T 29 S
R S35 | S36 R
7 S 2 | S 1 7
W T 30 S W
No new accessories. Corner is at the NW corner of old growth
timber.

GL0 Resurvey - James E. Jelley, Cadastral Surveyor - Group #
1007 - Aug/Mar 1980-82 (DCS0 records Vol. 43 Pg. 16791-92)

Monumented with an iron post, 1 ¼" diam., firmly set,
projecting 10" above ground, with brass cap mkd.
County Surveyor's Office
T 29 S R 7 W
S 35 | S 36
S 2 | S 1
T 30 S
1978
from which the bearing trees mkd. by Markham:
A madrone, 21" diam., bears N.37°E., 52½ lks., with
fragmentary scribe marks visible on open blaze
A madrone, 36" diam., bears S.21°E., 68 lks., with
fragmentary scribe marks visible on open blaze
A madrone, 24" diam., bears S.81½°W., 54½ lks., with
fragmentary scribe marks visible on open blaze.
A madrone, 32" diam., bears N.21°W., 53 lks., with
fragmentary scribe marks visible on open blaze
and the remaining original bearing tree
A madrone, 23" diam., bears S.68°E., 42 lks., with
fragmentary scribe marks visible on open blaze.
and new bearing trees
A fir, 13" diam., bears S.23°W., 29½ lks., mkd. T30S R7W
S2 BT.
A fir, 9" diam., bears N.6½°W., 42 lks., mkd. T29 R7W S35
BT.

Fd. and used in BLM resurvey by Dale Bedell, Group #1660,
surveyed April/June 1993 - (DCS0 Records, Vol. 51 Pg. 19362)