

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7234)

Set ¼ sec. post, from which
A Pine 48" dia., bears N.20°E., 22 lks. dist.
A Pine 30" dia., bears S.30°W., 31 lks. dist.

Survey by John H. Markham, Jr. - Wit: J.H. Brown - May 10, 1951 - C.S. File 40/311

I rescribed both original BTs.
At corner point, Set 1" x 30" Iron pipe, from which original bearing trees bear
A Pine 46" dia., bears N.32°E., 18.5 ft.
A Pine 34" dia., bears S.30°W., 21.5 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman crew - Feb. 1964 - C.S. File 53/40-51

Found - 1" Iron pipe at corner and both BTs as recorded by Markham. NE. BT, now stump.
New BT - 18" Laurel bears North, 35.7 ft. scribed ¼ S24 CSBT.

BLM resurvey by James E. Jelley and Charles E. Akin, Cadastral Surveyors, under Group #'s 734 and 829, surveyed April 1971/Oct. 1973 - (DCSO records Vol. 37 Page(s) 15148-49)

The ¼ sec. cor., perpetuated and recorded by Markham in 1951, and subsequently perpetuated by Byron in 1964, monumented with an iron pipe, 1" dia., firmly set, projecting 8" above ground, from which the remains of the original bearing trees:
A sawed Pine stump 44" dia., bears N.32°E., 30 lks. dist. with scribe marks ¼ BT visible on opened blaze. (Rec. N.20°E., 22 lks.)
A Pine snag 26" dia., bears S.30°W., 31 lks. dist. with fragmentary scribe marks visible on decayed blaze.
and a bearing tree mkd. by Byron
A Laurel 18" dia., bears North, 54 lks. dist. with scribe marks ¼ S24 CS visible on partially open blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
1/4 $\frac{S\ 24}{S\ 25}$
T 30 S R 7 W
1971

(Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which a new bearing tree:
A Fir 4" dia., bears S.65°W., 13 lks. dist. mkd. ¼ S25 BT.
Deposit the iron pipe alongside the iron post.

Brent Knapp - For: Roseburg Resources Co. - 8/2023 - M182-53

Found - BLM brass cap
Rotten Pine stump, open blaze w/no remaining marks;
N.32°E., 19.8'
2'x26" Pine stump, fragmented markings on rotten
blaze; S.30°W., 19.8'
Madrone cluster grown out of old BT, North 35.6'
New - 7" Madrone, scribed "¼ S24 BT" N.74°E., 7.4'
6" Madrone, scribed "¼ S25 BT" S.46°E., 6.1'
7" Madrone, scribed "¼ S25 BT" S.2°W., 2.5'
7" Madrone, scribed "¼ S24 BT" N.25°W., 21.2'