

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7235)

-----  
Set ¼ sec. post, from which  
A Laurel 60" dia., bears N.65°E., 39 lks. dist.  
A Laurel 6" dia., bears S.5°W., 71 lks. dist.

Survey by Claude Kerr - June 6, 1953 - C.S. File 41/160

-----  
I found the orig. 60" Laurel BT, bearing N.65°E., 39 lks.  
Set a 4" x 4 ft. Cedar stake for ¼ cor. stake marking it ¼ S13 and ¼ S24. The other BT has been destroyed.

Survey by Howard Johnstone - For: Roseburg Lumber Co. - May 28, 1962 - C.S. File 51/163-2

-----  
Found - 60" Laurel N.65°E., 35 lks., dead.  
Set 1¼" x 24" iron pipe, from which scribed:  
18" D.Fir N.18°W., 22.0 ft.  
16" D.Fir S.72°W., 25.5 ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2191, Surveyed April/May 2008 - (DCSO records Vol. 56 Page(s) 22132)

-----  
The ¼ sec. cor. of secs. 13 & 24, perpetuated by Kerr, in 1953, subsequently perpetuated by Johnstone, in 1962, monumented with an iron pipe, 31" long, 1½" dia., firmly set, projecting 7" above ground, from which the remains of the original bearing trees

A decayed madrone stump, size indeterminate, bears N.65°E., 25.7 ft., with no marks visible.

A decayed madrone stump, size indeterminate, bears S.5°W., 46.9 ft., with no marks visible.

and the remains of bearing trees mkd. by Johnstone

A sawed, decayed fir stump, size indeterminate, bears S.73°W., 24.5 ft., with no marks visible.

A sawed, decayed fir stump, size indeterminate bears N.17½°W., 22.2 ft., with no marks visible.

At the cor. point

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd.

T30S R7W  
¼ S 13  
S 24  
2008

from which new bearing trees  
continued next page

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 13" dia., bears South, 16.1 ft., mkd. ¼ S24 BT.  
A fir, 5" dia., bears N.67¾°W., 3.0 ft., mkd. ¼ S13 BT.  
Place iron pipe inside the stainless steel post and deposit a magnet in a white plastic case at the base of the stainless steel post.

Brent Knapp - For: Roseburg Resources Co. - 8/2023 - M182-53  
-----  
Found - 2008 BLM brass cap  
Rotten Madrone stump; N.65°E., 25.7'  
Rotten Madrone stump; S.5°W., 46.9'  
Rotten Fir stump; S.73°W., 24.5'  
Rotten Fir stump; N.17½°W., 22.2'  
15" Fir, healed scar; South 16.1'  
8" Fir, healed scar; N.67¾°W., 3.0'  
New - 7" Madrone, scribed "¼ S13 BT" N.16°E., 14.0'  
6" Madrone, scribed "¼ S13 BT" N.59°E., 10.3'