

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7236)

Set ¼ sec. post, from which
A Fir 60" dia., bears N.60°E., 71 lks. dist.
A Pine 48" dia., bears S.70°W., 38 lks. dist.

BLM resurvey by James E. Jelley and Charles E. Akin, Jr., Cadastral Surveyors, under Group #'s 734 and 829, surveyed April 1971/Oct. 1973 - (DCSO records Vol. 37 Page(s) 15149-50)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
T 30 S R 7 W
1/4 S 12
S 13
1973

from which
A W.Fir 12" dia., bears S.2°E., 47 lks. dist. mkd. ¼ S13 BT.
A Cedar 8" dia., bears N.81°W., 25 lks. dist. mkd. ¼ S12 BT.

Survey by Mark F. Smalley - For: Roseburg Forest Products - Feb. 1995 - M 121-59

Found - 1973 Cadastral brass cap and iron pipe.
18" Cedar N.81°W., 16.5 ft., healed.
16" Fir S.2°E., 31 ft., healed.
Scribed -6" Fir N.42°W., 16.1 ft. "¼ S BT".
8" Fir N.62°E., 22.9 ft. "¼ S BT".

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2191, Surveyed April/May 2008 - (DCSO records Vol. 56 Page(s) 22138-9)

The ¼ sec. cor. of secs. 12 and 13, perpetuated by Smalley, in 1995, monumented with an iron post, 2½" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd. from which bearing trees mkd. by Jelley and Akin
A fir, 18" dia. bears S.2°E., 31.0 ft. with a healed blaze
A cedar, 21" dia., bears N.81°W., 16.5 ft., with a healed double blaze.
and bearing trees mkd. by
continued next page

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 13" dia., bears N.58¼°E., 23.1 ft., with a healed blaze.
A fir, 12" dia., bears N.42½°W., 15.6 ft., with a healed blaze.
Corner is located on a SE. slope.