

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7237)

Set ¼ sec. post, from which
A Fir 72" dia., bears N.50°E., 24 lks. dist.
A B.Oak 24" dia., bears S.40°W., 28 lks. dist.

Douglas Co. Surveyors Office - Vernon R. Tracy; Mike Stone; J. Barnett, crew - Sept. 3, 1964 - C.S. File 53/40-86

Found - Orig. 72" D.Fir N.50°E., 15.8 ft. shows bark scribe.
Orig. 24" now 30" B.Oak S.40°W., 18.5 ft., shows good scar. Did not open.

Set brass cap at intersection of dist. and brg. to Fir. Bearing to Oak is S.45°W., Brass cap mkd. County Surveyors Office 1964 T30S R7W ¼ S1 S12.

New BTs -13" D.Fir N.20°E., 41.8 ft. mkd. ¼ S1 CS BT.
16" D.Fir S.2½°E., 31.6 ft. mkd. ¼ S12 CS BT.

Fd. and used in BLM resurvey by James E. Jelley, Cadastral Surveyor under Group #1007, surveyed Aug. 1980/March 1982 - (DCSO records, Vol. 43 Pg.16788)

Fd. and used in BLM resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1660, surveyed April/June 1993 - (DCSO records, Vol. 51 Pg. 19363)

Survey by Mark F. Smalley - Roseburg Resources Co. - Feb. 1995 - M 121-59

Found - 1964 County brass cap & Iron pipe
72" fir, N.50°E. 15.8', bark scribe original BT.
15" fir, N.20°E. 41.8', healed.
28" oak, S.40°W. 18.5', healed original BT.
16" fir, S.2½°E. 31.6', stump.
Scribed- 6" fir, N.44°W. 9', "¼ S BT".