

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 640640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM survey by Dale T. Bedell, Cadastral Surveyor, under Group #1660, Surveyed April/June 1993 - (DCSO records Vol. 51 Page(s) 19364)

The center 1/4 cor. of sec. 1, established and recorded by Bruce R. Rogers, in 1974 (M 49-53) and is accepted as the corner, monumented with an iron pipe, 1" dia., firmly set, projecting 9" above the ground.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, directly over the iron pipe, with brass cap mkd:

T 30 S R 7 W
C 1/4 S 1
1993

from which

A Cedar 9" dia., bears S.73 3/4°E., 195 lks. dist. mkd. C¼ S1 BT.

The southerly trunk of a double trunked Cedar, 17" dia., bears N.4½°W., 119½ lks. dist. mkd. C¼ S1 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

(Note: the survey map M 49-53 does not show visually, a corner set at the center of section 1) May 1996, V.Laugen