

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION ¼ sec cor to 1 & 36 of T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO Survey - W.H. Byars - contract #152 dated Jun 3, 1871 (DCSO records Vol. 17 Pg. 7231)</p> <p>-----</p> <p>Set ¼ sec. post from which</p> <ul style="list-style-type: none">A pine, 60" diam., bears N.40°E., 214 lks.A pine, 30" diam., bears S.15°W., 403 lks.
<p>Briggs - Nov. 1887 - F.B. #3 Pg. 8</p> <p>-----</p> <p>Set post marked BT</p> <ul style="list-style-type: none">Pine 30" diam., bears N.27°E., 254 lks.Pine 20" diam., bears S.22°E., 353 lks.
<p>John H. Markham Jr. - for Stomar Lumber Co. - Apr/Sep 1956 - C.S. 42/192-3</p> <p>-----</p> <p>Point for corner determined by OBT:</p> <ul style="list-style-type: none">A 67" pine stump bears N.40°E., 141 ft., fd. scribe <p>At corner point set 2"x16" solid steel shaft, from which:</p> <ul style="list-style-type: none">A 8" W.Oak, bears N.23°W., 38 ft., mkd. ¼ S36 BTA 15" Cedar, bears S.18°E., 39.6 ft., mkd. ¼ S1 BT <p>Road bears East 230 ft.</p>
<p>BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1660, Surveyed April/June 1993 - (DCSO records Vol. 51 Page(s) 19361)</p> <p>-----</p> <p>At the ¼ sec. cor., perpetuated and recorded by Markham in 1956, monumented with an iron rod, 18" long, 2" dia., firmly set 10" in the ground, from which the remains of the original bearing trees:</p> <ul style="list-style-type: none">A rotted Pine stump 66" dia., bears N.40°E., 217 lks. dist., with axe marks on a rotted blaze. (Rec. 214 lks.)A roothole, bears S.18°W., 403 lks. dist., with a down Pine alongside, 30" dia., with scribe marks ¼ S visible on an opened blaze. (Rec. S.15°W.) <p>and bearing trees mkd. by Markham</p> <ul style="list-style-type: none">A Cedar 28" dia., bears S.18°E., 60 lks. dist., with a healed blaze.A W.Oak 19" dia., bears N.22°W., 57½ lks. dist. with a healed blaze. <p>At the corner point</p> <p>Set an stainless steel post, 28" long, 2 1/2" dia., 12" in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:</p> <p style="text-align: right;">T29S R7W 1/4 $\frac{S\ 36}{S\ 1}$ T30S R7W 1993</p> <p>(Cont. Next Page)</p>

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & 36 of T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Deposit a white "DEEP-1" magnetic marker at base and the iron rod alongside the stainless steel post.

From this point, the United States Coast and Geodetic Survey triangulation station "BUCK MOUNTAIN" bears S.55°35'00"W., 243.130 chs. dist. (mean bearing and sea level distance), monumented with a brass disk, 3" dia., cemented into solid rock, mkd. BUCK MTN 1942.

Mark Smalley - For: Roseburg Resources - 1/ 2005 - C.S. File 65/54-4

Found - BLM IPBC - solid in rock mound
20" W.Oak N.23°W., 38.0 healed (BLM N.22°W.)
30" Cedar S.18°E., 39.6 healed
67" Pine stump N.40°E., 141.0 rotten
New - 11" cedar S.18°W., 9.3 scribed "¼ S BT"
10" Cedar N.72°W., 5.8 scribed "¼ S BT"