

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Tsp. Cor. (SE Cor. Sec. 36)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7191)

-----  
Set post for cor. to Tps. 30 and 31, Rgs. 6 & 7, from which  
A Laurel 6" dia., bears S.51°W., 27 lks. dist.  
A Laurel 6" dia., bears S.60°E., 20 lks. dist.  
A Laurel 8" dia., bears N.45°W., 200 lks. dist.  
A Laurel 12" dia., bears N.38°E., 148 lks. dist.

Cor. Fd. and used in GLO survey by W.H. Byars, under Contract #448 dated June 13, 1882 (DCSO records, Vol. 19 Pg. 7956)

John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: J.R. Markham - July/Aug. 1961 - C.S. File 42/288-1

-----  
As determined by O.B.T.s  
23" Laurel N.45°W., 134.0 ft.  
24" Laurel snag N.38°E., 100.0 ft.  
30" Laurel snag S.60°E., 18.0 ft.  
At corner point, Set 3/4" x 30" I.Pipe, from which  
8" Fir bears South 53.4 ft. mkd. "S6 X BT."  
Large rock 6' x 6' x 10' bears S.18°W., 33.0 ft. at North face.  
5" Fir S.85°W., 13.8 ft. mkd. "S1 BT".  
6" Fir N.15°W., 9.0 ft. mkd. "S36 BT".  
6" B.Oak N.72°E., 26.2 ft. mkd. "S31 BT".

BLM Resurvey by James Jelley, under Group #585 - Surveyed, July/Aug. 1965 (DCSO records, Vol. 33 Page 13815)

-----  
The Tsp. corner, perpetuated and recorded by Markham, 1961, monumented with an iron pipe 3/4" dia., loosely set, extending 18" above ground, from which the remaining original bearing trees:

A rotted Madrone stump 24" dia., bears N.36°E., 148 lks. dist., with old axe marks visible on section of blaze. (Rec. N.38°E.)  
The rotted remains of a Madrone stump, size indeterminate bears S.51°W., 27 lks.  
A Madrone 16" dia., bears N.45°W., 212 lks. dist., with opened and burned blaze. (Rec., 200 lks.)  
and bearing trees mkd. by Markham:  
A B.Oak 6" dia., bears N.72°E., 39½ lks. dist., with scribe marks CS visible on partly healed blaze.  
A Fir 9" dia., bears South, 81 lks. dist., with healed double blaze.  
A Fir 6" dia., bears S.85°W., 21 lks. dist., with healed double blaze. (Cont. Next Page)



TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Tsp. Cor. (SE Cor. Sec. 36)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Corner is located on an E. facing slope.  
The geographic position in NAD 1983 (2011)  
Latitude: 42°54'49.00" N. Longitude: 123°27'59.34" W.