

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 36; & 31, T30-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7191)

Set quarter sec. post, from which
A Pine 5" dia., bears S.78°E., 204 lks.
A Pine 22" dia., bears S.25°W., 203 lks.

Not Fd, DCSO 3/1965 - C.S. File 53/40-62

Mark Smalley - For: Roseburg Resources - July 1992 - M 112-52

Set 5/8" x 48" Iron rod and aluminum cap.
New BTs -9" Madrone bears N.41°W., 22.8 ft. scribed "¼ S36 BT"
18" Pine bears S.88°E., 56.5 ft. scribed "¼ S31 BT"
18" Pine bears N.81°W., 45.2 ft. scribed "¼ S36 BT"
7" Pine bears N.06°E., 13.3 ft. scribed "¼ S BT".

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2928 - surveyed July /Aug. 2018 - (DCSO records Vol. 59 Page(s) 23660-1)

The ¼ sec. cor. of secs. 31 and 36, reestablished by proportionate measurement by Smalley, in 1992; there is no remaining evidence of the original cor., therefore this point is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron rod, 5/8" dia., firmly set, projecting 4" above ground, no cap, from which the bearing trees mkd. by Smalley

A pine, 19" dia., bears N.86¼°W., 44.9 ft., with a healed blaze.

A madrone, 12" dia., bears N.48¼°W., 22.0 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, directly over the iron rod, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T 30 S
1/4

R R
7 S 36 | S 31 6
W W

2018

Corner is located on a SE facing slope.