

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T30-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7191)

Set post, cor. to secs. 30, 31, 25 and 36, from which
A Pine 20" dia., bears S.23°E., 178 lks.
A Pine 20" dia., bears N.18°E., 112 lks.
A Pine 30" dia., bears S.34°W., 161 lks.
A Pine 22" dia., bears N.35°W., 120 lks.

A. R. Evans - For: D. Kartes - Wit: G.E. Johnson - June 15, 1953 - C.S. File 41/252-1

Found - 22" Pine N.35°W., 12 lks.
20" Pine S.23°E., 178 lks., both dead and down.
Set 4" x 4" x 48" Pine stake.
New BTs - 14" Pine S.44½°W., 31.6 ft. mkd. "T30S R7W S36".
18" Pine S.15½°E., 8.8 ft. mkd. "T30S R6W S31".
16" Pine N.19°E., 48.5 ft. mkd. "T30S R6W S30".
14" Pine N.47°W., 14.5 ft. mkd. "T30S R7W S25 RE 2741 BT".

Doug. County Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman - Nov/Dec. 1963 - C.S. File 53/40-1

Found - All BTs as recorded by Evans. SW BT now snag.
Find base corner stake.
Set Brass cap at cor. mkd: County Surveyor's S25|S30 T30S
Office 1963 R7W S36|S31 R6W
New BT - 10" R.Fir bears S.27°W., 67.5 ft. scribed S36 T30S
R7W CS BT.

Fd. OK, BLM resurvey by Jelley and White, 1971/1973 (DCSO records, Vol. 37 Pages 15139-40)

Fd. OK, July 1992, Mark Smalley, M 112-52

Mark Smalley - For: Roseburg Resources Co. - June 1999 - M 133-9

Found - 1963 County brass cap on I.P.
24" Pine N.19°E., 47.5 ft. scribe visible.
22" Pine N.35°W., 79.2 ft. duff pile orig.
20" Pine S.23°E., 117.5 ft. duff pile orig.
23" Pine S.15½°E., 8.8 ft. scribe visible.
14" Fir S.27°W., 67.5 ft. healed.
New BT - 8" Fir S.34°W., 45.1 ft. "S 36 BT"

cont.

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T30-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2928 - surveyed July /Aug. 2018 - (DCSO records Vol. 59 Page(s) 23661

The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., reported by Jelley and Akin Jr. in 1971-73; subsequently perpetuated by Smalley, in 1999; monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with a brass cap (properly) mkd.

from which the bearing trees reported by Jelly and Akin Jr.

A pine, 28" dia., bears N.19°E., 47.5 ft., with a healed blaze.

A pine, 24" dia., bears S.9°E., 8.6 ft., with scribe marks B and other illegible scribe marks visible on partially healed blaze.

A fir, 19" dia., bears S.26½°W., 65.3 ft., with a healed blaze.

and a bearing tree mkd. by Smalley

A fir, 15" dia., bears S.33°W., 44.4 ft., with a healed blaze.

A metal fence post is alongside the cor.