

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T30-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Pages 7190-91)

Set post, cor. to secs. 19, 30, 24 and 25, from which
 A Pine 18" dia., bears S.60°W., 70 lks. dist.
 A Pine 4" dia., bears S.35°E., 108 lks. dist.
 A Pine 6" dia., bears N.60°W., 207 lks. dist.
 A Pine 12" dia., bears N.48°E., 124 lks. dist.

John H. Markham, Jr. - Wit: J.H. Brown - May 10, 1951 - C.S. File 40/311

Determined by chopping 3 hours on 30" Pine.
 Pine 30" dia., (now chopped 1/2 in two) bears N.48°E., 82.0 ft. found old scribe.
 Pine 36" dia., bears S.60°W., 49.0 ft. I remarked this O.B.T., "S25 BT".
 At corner point, set 1" x 30" Iron pipe, from which
 Pine 14" dia., bears N.85°W., 50.5 ft. mkd. S24 BT.
 Pine 14" dia., bears S.78°E., 37.0 ft. mkd. S30 BT.

Doug. County Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman - Nov/Dec. 1963 - C.S. File 53/40-34

Found - Orig. 18" now 40" Pine S.60°W., 46.2 ft. shows good scar.
 Orig. 12" now 30" Pine N.48°E., 81.8 ft. previously opened, shows good scribing.
 No other orig. BTs found.
 Also find 1" I.Pipe at corner.
 We find 18" Pine N.84°W., 49.7 ft., shows good scribing. Markham' axe used to open the NE BT couldn't have been very sharp.

Set Brass cap at cor. mkd: County Surveyors Office 1963

R7W	S 24	S19	R6W	T30S
	S 25	S30		

New BT -25" Pine bears S.40°E., 24.0 ft. scribed S30 T30S R6

Fd. OK, BLM resurvey by Jelley and White, 1971-1973, (DCSO records, Vol. 37 Pages 15141-42)

Fd. OK, May 6, 1991, DCSO, C.S. File 64/15-8

continued next page

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Cor. Secs. 24 & 25; 19 & 30, T30-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Mark Smalley - For: Roseburg Resources Co. - Feb. 1999 -
M129-43

Found - 1963 County brass cap on IP
44" Pine S.60°W., 46.2 ft., dead. OBT
17" Pine S.78°E., 39.6 ft., (37.0 ft.) snag.
28" Pine S.40°E., 24.0 ft., healed.
33" Pine N.48°E., 81.8 ft., scribe visible. OBT
24" Pine N.85°W., 49.7 ft. (50.5 ft) healed.
Scribed- 15" I.Cedar S.41°W., 3.4 ft., "S 25 BT"