

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T30-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Pages 7189-90)

-----  
Set post, cor. to secs. 7,18, 12 and 13, from which  
A Laurel 16" dia., bears S.50°E., 25 lks. dist.  
A Laurel 20" dia., bears S.25°W., 75 lks. dist.  
A Laurel 20" dia., bears N.89°W., 55 lks. dist.  
A Laurel 7" dia., bears N.79°E., 43 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - July 8, 1960 - C.S. File 52/25-7

-----  
Found - Orig. 20" now down 30" Laurel, N.89°W., 36.3 ft., shows good reverse scribing "B" "2".  
Orig. 20" now 30" Laurel S.25°W., 49.5 ft. center rotted.  
Orig. 7" now down & rotted 12" Laurel, N.79°E., 28.4 ft.

No trace of orig. SE BT found.

Set Brass cap at cor. mkd: County Surveyor's 

S12	S 7	T30S
R7	S13   S18	R6

New BTs -14" R.Fir bears N.18°W., (? ft) scribed S12 T30S R7W CSBT  
12" R.Fir bears N.20°E., 15.5 ft. scribed S7 T30S R6W CS BT.  
8" R.Fir bears S.23°W., 17.8 ft. scribed S13 T30S R7W CS BT.  
8" R.Fir bears S.29°E., 26.8 ft. scribed S18 T30S R6W CS BT.

BLM resurvey by Jelley and White under Group #'s 551 and 350 Surveyed May 1963/July 1964 (DCSO recs, Vol. 32 pg 13581-82)

-----  
The Sec. cor. perpetuated and recorded by Byron, 1960, monumented with an I.P. 1" dia., 12" above ground, firmly set, with properly mkd. brass cap.

from which the remaining orig. bearing trees  
A down and rotted Madrone 12" dia., bears N.79°E., 43 lks. dist., no marks visible.  
A Madrone 30" dia., bears S.25°W., 75 lks. dist., with rotted center, no marks remaining.  
A down madrone 30" dia., bears N.89°W., 55 lks. dist., with fragmentary scribe marks visible in the negative on section of overgrowth.

and bearing trees mkd. by Byron

A Fir 13" dia., bears N.20°E., 24 lks. dist., with illegible scribe marks visible on partially healed double blaze. (Cont. Next Page)

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T30-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 10" dia., bears S.29°E., 40 lks., with illegible scribe marks visible on partially healed double blaze.  
A Fir 9" dia., bears S.23°W., 27 lks., with illegible scribe marks visible on partially healed double blaze.  
A Fir 15" dia., bears N.18°W., 65 lks., with illegible scribe marks visible on partially healed double blaze.  
Add marks BLM 1964 to bottom of brass cap.

BLM resurvey by Jelley and Akin, under Group #'s 734 and 829  
Surveyed April 1971/Oct 1973 (DCSO recs, Vol 37 Pg 15143-44)

-----  
The Sec. cor., perpetuated and recorded by Byron, 1960, monumented with an I.P. 1" dia., firmly set, projecting 12" above ground with properly mkd. brass cap.  
from which the remains of the original bearing tree  
A root hole bears N.89°W., 55 lks. dist., with a down Madrone alongside 30" dia., with healed blaze.  
and bearing trees mkd. by Byron  
A Fir 15" dia., bears N.20°E., 24 lks., with healed double blaze.  
A Fir 10" dia., bears S.29°E., 40 lks., with healed blaze.  
A root hole bears S.23°W., 27 lks., with a down Fir alongside, 30" dia., with healed double blaze.  
A Fir 8" dia., bears N.18°W., 65 lks., with healed double blaze.  
and a new bearing tree  
A Fir 8" dia., bears S.25°W. 53 lks. mkd. T30S R7W S13 BT.

Mark F. Smalley - Roseburg Resources - Feb. 1995 - M 121 - 59

-----  
FOUND - 1960 County brass cap & Iron pipe  
17" fir, N.18°W. 43.4', healed  
20" fir, N.20°E. 15.5', stump  
14" fir, S.29°E. 26.8', healed  
10" fir, S.23°W. 17.8', healed down  
SCRIBED- 12" fir, S.89°W. 24.5', "S 13 BT"

DCSO-GIS Corner visitation - 3/1/2004 - Typed: 2/9/2011 -  
C.S. File 67/33-1

-----  
Monument - 1.25" IP/BC  
Comment - OK

continued next page

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T30-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2191, Surveyed April/May 2008 - (DCSO records Vol. 56 Page(s) 22130-1)

-----  
The cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., perpetuated by Smalley, in 1995, monumented with an iron post, 1¼" dia., firmly set, projecting 11" above ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree

A roothole bears N.89°W., 36.3 ft., alongside of which is a down, decayed madrone, size indeterminate, with no marks visible.

and the remains of BTs mkd. by Byron, reported by Jelley and Akin

A sawed fir stump, 21" dia., bears N.20°E., 15.8 ft., with a healed blaze.

A fir, 20" dia., bears S.29°E., 26.4 ft., with a healed blaze.

A roothole bears S.23°W., 17.8 ft., alongside of which is a down, decayed fir snag, size indeterminate, with no marks visible.

A fir snag, 17" dia., bears N.18°W., 42.9 ft., with a healed double blaze.

and a bearing tree mkd. by Smalley

A fir, 14" dia., bears S.89°W., 24.1 ft., with a healed blaze.

and new bearing trees

A madrone, 10" dia., bears N.57½°E., 94.2 ft., mkd. T30S R6W S7 BT in the bark.

A fir, 12" dia., bears N.78¾°W., 21.9 ft., mkd. T30S R7W S12 BT.

Corner is located on an E. slope and 60 ft. W. of a shallow ravine, drains South.