

TOWNSHIP 30 RANGE 07 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 12; & 7, T30-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7189)

-----  
Set quarter sec. post, from which a  
W.Oak 7" dia., bears N.50°E., 130 lks.  
W.Oak 12" dia., bears S.65°W., 79 lks.

Doug. County Surveyors Office - James Byron, Deputy - M. Darby; Wm. Stoffel - June 1963 - C.S. File 49/139-106

-----  
Found - Orig. 7" now down, 10" Oak N.50°E., 85.8 ft. previously opened, shows good scribing "BT".  
Stump hole that checks for orig. SW BT.

Set Brass cap at cor. mkd: County Surveyor's Office, 1963  
¼ R7W S12|S7 R6W T30S

New BTs -16" R.Fir bears N.33°E., 6.8 ft. scribed ¼ S7 CSBT  
10" R.Fir bears S.18°W., 15.3 ft. scribed ¼ S12 CSBT

BLM resurvey by Jelley and White, under Group #'s 350 and 551 Surveyed May 1963/July 1964 (DCSO records, Vol. 32 Page 13582)

-----  
The 1/4 Cor. perpetuated and recorded by Byron, 1963, monumented with an I.P. 1" dia., 16" above ground, firmly set, with properly mkd.brass cap.

from which the remaining original bearing tree  
A down Oak 10" dia., bears N.50°E., 128½ lks. with scribe marks S BT and other fragmentary marks visible on opened blaze. (Rec. dist. 130 lks.)

and bearing trees mkd. by Byron  
A Fir 15" dia., bears N.33°E., 11 lks. dist., with scribe marks ¼ S7 CS BT visible on double blaze.

A Fir 10" dia., bears S.18°W., 23½ lks. dist., with scribe marks ¼ S12 CS BT visible on double blaze.

Add marks BLM 1964 to bottom of brass cap.

See BLM for a 1977 Admin. Survey)

Mark F. Smalley - Roseburg Resources - Feb. 1995 - M 121- 59

-----  
FOUND - 1963 County brass cap & Iron pipe  
28" fir, N.33°E. 6.8', healed  
14" fir, S.18°W. 15.3', healed  
SCRIBED- 7" cedar, N.41°W. 18.5', "¼ S BT"  
22" fir, S.78°E. 21.2', "¼ S BT"