

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Section 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7372)

Set post, cor. of Tps. 30 and 31 S., Rgs. 8 and 9 W., from which

- A Fir 12" dia., bears N.2°E., 43 lks. dist.
- A Fir 10" dia., bears N.63°W., 25 lks. dist.
- A Fir 15" dia., bears S.75°W., 38 lks. dist.
- A Fir 30" dia., bears S.40°E., 57 lks. dist.

BLM Resurvey by C. Albert White; Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Surveying Technician, under Group #446, Surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 31 Page(s) 13189)

The cor. of Tps. 30 and 31 S., Rs. 8 and 9 W., determined from the remains of the original bearing trees:

- A down Fir 27" dia., bears N.2°E., 36 lks. dist. 43 lks. slope dist., mkd. with a healed blaze. (Rec. dist. 43 lks.)
- A Fir 51" dia., bears S.38°E., 59 lks. dist. to the face, mkd. with old axe marks and rotting bark blaze. (Rec. S.40°E., 57 lks.)
- A Fir 35" dia., bears S.68°W., 38 lks. dist. mkd. with a healed blaze. (Rec. brg. S.75°W.) Remarked T31S R9W S1 BT)
- A Fir 27" dia., bears N.72½°W., 25 lks. dist., mkd. with a healed blaze. (Rec. brg. N.63°W.) Remarked T30S R9W S36 BT.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 30 S	
R 9 W	R 8 W
S 36	S 31
S 1	S 6
T 31 S	
1962	

from which

- A Fir 35" dia., bears N.54¼°E., 53 lks. dist. mkd. T30S R8W S31 BT.
- A Fir 15" dia., bears S.22½°E., 25 lks. dist. mkd. T31S R8W S6 BT.

Fd. BC & 4 BTs by Don Garrett - For: US Dept. Interior, BLM, contract No. 53500-CT2-334(N) - Sept 1972 Filed 2/10/1982 (added to record 10/2/2023)- M91-10_____