

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; and 13, T30-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7370)

Set ¼ sec. post, from which
A W.Oak 12" dia., bears N.42°E., 36 lks. dist.
A W.Oak 10" dia., bears S.35°W., 69 lks. dist.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - May 28, 1962 - C.S. File 51/163-3

Found - W.Oak, S.35°W., 45.5 ft., down, no visible scribing.
12" W.Oak N.42°E., 23.8 ft., down, scribe visible.
Set 1" x 36" Iron pipe.
Scribed- 16" D.Fir S.43°W., 40.0 ft.
6" D.Fir N.55°E., 9.7 ft.

Fd. OK, June 1988 by H. Johnstone - M 106-51

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2009, surveyed July/Aug. 2002- (DCSO rec. Vol. 54 Page(s) 21065-6)

The ¼ sec. cor. of secs. 13 & 18, on the E. bdy. of the Tp., perpetuated by Johnstone, in 1962, monumented with an iron post, 1" dia., firmly set, projecting 16" above ground, with no cap, from which the remains of an orig. bearing tree
A decayed stump, size & species indeterminate, bears S.31°W., 40.7 ft., with no marks visible. (Record, oak, S.35°W., 45.5 ft.)
and bearing trees mkd. by Johnstone
A fir, 17" dia., bears N.55°E., 9.7 ft., with healed blaze
A fir, 23" dia. bears S.41¼°W., 39.2 ft. with healed blaze
At the corner point
Cement a brass tablet, 2½" dia., with stem, 2½ ins. long, into top of iron post, mkd.
T 30 S
R 9 W R 8 W
¼
S 13 | S 18
2002