

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & S. 1, T30-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7369)

Set ¼ sec. post, from which
A Fir 18" dia., bears S.80°E., 37 lks. dist.
A Fir 20" dia., bears S.69°W., 37 lks. dit.

Survey by Forrest J. Hales - For: Moore Mill & Lumber Co. - April/May 1965 - C.S. file 54/6

Set 1/2" Pipe post, from which
8" D.Fir bears N.68°E., 3.2 ft. mkd. "BT S6 30-8"
6" W.Fir bears West 9.7 ft. mkd. "BT S1"
A Fir stub with an old yellow tag bears N.69°E., about 40 to 50 ft.
Corner is about 150 ft. West of the creek.

Mark Smalley - For: Roseburg Resources & Moore Mill - 8/2002 - M 137-50

Found - ¾" iron pipe (Hales, C.S. 54/6)
19" Fir N.62°E., 3.3' healed (rec. N.68°E., 3.2')
17" Fir West 9.1' healed (rec. West 9.7')
Scribed- 12" W.Fir N.8°E., 10.9' "¼ S6 BT"
6" Fir S.48°W., 17.2' "¼ S1 BT"