

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 139700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 31 only, T29-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6578)

Set ¼ sec. post, from which
A Fir 15" dia., bears North, 16 lks. dist.
A Chinquapin 12" dia., bears S.20°W., 29 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Sept. 1958 - C.S. File 49/100-34

Found - Orig. 15" now 24" stump previously opened, shows good scribing "BT".
Stump hole that checks bearing and distance for orig. SW. BT.

Set Brass cap at cor. mkd: County Surveyors Office
¼ S 31 T 29 S R8W
S 6 T 30 S
1958

New BTs- 15" R.Fir bears N.37°E., 39.3 ft. scribed S31 ¼ CSBT
22" R.Fir bears S.22°E., 47.3 ft. scribed ¼ S6 CSBT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #584 - Surveyed July 1965 - (DCSO records Vol. 33 Page(s) 13879)

The ¼ sec. cor., perpetuated and recorded by Byron in 1958, monumented with an iron post, 1½" dia., firmly set, extending 12" above ground, with brass cap mkd. in 1958, from which the remains of the original bearing trees:

A sawed Fir stump 24" dia., bears North, 16 lks. dist. mkd. BT on opened blaze.
A stump hole bears S.20°W., 29 lks. dist. and bearing trees mkd. by Byron:
A Fir 16" dia., bears N.36°E., 59½ lks. dist., mkd. with a partially healed double blaze.
A Fir 21" dia., bears S.24½°E., 72½ lks. dist., mkd. with a partially healed double blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd: T 29 S R 8 W
¼ S 31
1965

from which a new bearing tree:
A Fir 18" dia., bears N.66°W., 61 lks. dist. mkd. ¼ S31 BT
Reset the county iron post inverted alongside the iron post.

continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 139700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 31 only, T29-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Mark Smalley - For: Roseburg Resources & Moore Mill - 8/2002
- M 137-50

Found - 1965 BLM brass cap on an iron pipe & 1958 Douglas
Co. Surveyors brass cap on an iron pipe buried
inverted.

30" W.Fir N.64°W., 41.4' (rec. N.66°W., 40.3')

Scribed- 6" Fir N.27°W., 6.5' "¼ BT"

7" Fir N.59°E., 14.9' "¼ BT"

7" Fir N.13°W., 13.9' "¼ BT"