TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7359)

Set a fir post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which
A hemlock, 16" dia., bears N.50°E., 5 lks., mkd: ¼ S BT.
A hemlock, 6" dia., bears S.15°W., 26 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John Powell & crew - May 29, 1967 - C.S. File 53/67-20

Found - 6" hemlock, now 10" S.15°W., 17.2 ft., tree has been opened for scribe "4 S"
No trace of NE BT
Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1967 T30S R8W ¼ S 19 / S 30
New BTs- 12" Yew S.67°W., 19.8 ft. mkd: ¼ S30 CS BT.
31" D.Fir N.28°E., 20.4 ft. mkd: ¼ S19 CS BT.

BLM dependent resurvey James E. Jelley & Wayne L. Rogers, Cadastral Surveyor under Group # 1021 surveyed April 1980 (DCSO Vol. 45 Page(s) 17281)

The ¼ sec. cor. of sees. 19 and 30, perpetuated and recorded by Powell, in 1967, monumented with an iron post, 1¼" dia., firmly set, projecting 10", above ground, with brass cap (properly) mkd.
from which the remains of an original bearing tree
A root hole, bears S.15°W., 26 lks., with a down hemlock alongside, 10" dia., with scribe marks BT visible on partially open blaze.
and bearing trees mkd. by Powell
A fir, 33" dia., bears N.28°E., 31 lks., with healed blaze.
A yew, 12" dia., bears S.67°W., 30 lks., with scribe marks ¼ S30 BT visible on open blaze.