

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T31-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCS0 records Vol. 17 Page(s) 7308)

-----  
Set a Cedar post 4½ ft. long, 4" sq., 24" in the ground, for the cor. to secs. 5, 6, 31 and 32, marked T30S R8W S32 on the NE. face, T31S S5 on the SE. face; S6 on the SW. face; and S31 on the NW. face, also 5 notches on the E. and 1 notch on the W. angles of same, from which

- A Fir 12" dia., bears N.21°E., 56 lks. dist. mkd. T30S R8W S32 BT.
- A Fir 50" dia., bears S.16°E., 40 lks. dist. mkd. T31S R8W S5 BT.
- A Fir 14" dia., bears S.53°W., 28 lks. dist. mkd. T31S R8W S6 BT.
- A Fir 10" dia., bears N.40°W., 8 lks. dist. mkd. T30S R8W S6 BT.

BLM Resurvey by C. Albert White; Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Surveying Technician, Under Group #446, Surveyed Nov.1960/Sept. 1962 - (DCS0 records Vol. 31 Page(s) 13190-91)

-----  
The Sec. Cor., determined at record bearing and distance from the remaining original bearing trees:

- A Fir 62" dia., bears S.16°E., 40 lks. dist., mkd. T31S R8W S5 BT on bark blaze.
- A Fir snag 10" dia., bears N.40°W., 8 lks. dist., mkd. W on open blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 30 S R 8 W  
S 31 | S 32  
S 6 | S 5  
T 31 S  
1962

from which new bearing trees:

- A Fir 23" dia., bears N.85°E., 66 lks. dist. mkd. T30S R8W S32 BT.
- A Fir 15" dia., bears S.42°E., 25 lks. dist. mkd. T31S R8W S5 BT.
- A Cedar 6" dia., bears S.89°W., 43 lks. dist. mkd. T31S R8W S6 BT.
- A Fir 47" dia., bears N.21½°W., 43 lks. dist., mkd. T30S R8W S31 BT on bark blaze.

(Cont. Next Page)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Fd. BC & 5 BTs by Don Garrett - For: US Dept. Interior, BLM, contract No. 53500-CT2-334(N) - Sept 1972 Filed 2/10/1982 (added to record 10/2/2023)- M91-10

BLM resurvey by Charles E. Akin, Jr. Cadastral Surveyor, under Group #819, Surveyed Aug/Oct. 1973 - (DCS0 records Vol. 36 Page(s) 14937-38)

-----  
The Sec. Cor., monumented with an iron post 2½" dia., firmly set, protruding 6" above ground with brass cap mkd. in 1962, from which the remains of the original bearing trees:

A Fir snag 63" dia., bears S.16°E., 40 lks. dist., with fragmentary scribe marks visible on bark blaze.

A Fir snag 12" dia., bears N.40°W., 8 lks. dist., with no marks visible on rotted blaze.

and bearing trees mkd. by White, Corbin, and Beck:

A W.Fir 18" dia., bears S.42°E., 25 lks. dist., with healed blaze.

A Cedar 8" dia., bears S.89°W., 43 lks. dist., with scribe marks T31S R8W S6 BT visible on partially healed blaze.

A Fir 50" dia., bears N.21½°W., 43 lks. dist., with scribe marks T30S R8W S31 BT visible on bark blaze.

and bearing trees mkd. by John Powell, Deputy County Surveyor in 1967:

A W.Fir 14" dia., bears N.2½°E., 48 lks. dist., with healed blaze.

A W.Fir 25" dia., bears N.21°E., 56 lks. dist., with healed blaze.

(Note: the above BTs reported as to be by Powell were not of record in any materials given to me for this project. A "renewal" number was not listed on the "old" visual page.)  
V.Laugen, June 1997

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM - Snake Eyes - Task H - June 2023 - M178-75 A-E

-----  
Found - A ¾" BLM brass cap (properly mkd) 0.5 ft above ground from which:

A 12" rotted stump (18" high) bears N.30°W., 5.2 ft. (1973)

A 50" snag (80 ft high) bears N.16°W., 29.4 ft. with bark scribe mkd: T30S R8W S31 BT (1972)

A 59" stump metal top (8 ft high) bears S.16°E., 27.7 ft with healed blaze and BT sign (1972)

A 24" stump metal top bears S.42°E., 16.8 ft, trunk alongside (1960)

continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T31-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A 10" cedar bears S.89°W., 27.4 ft with healed blaze and BT sign (1960)

New - A 7" Fir bears N.6°W., 27.5 ft mkd: T30S R8W S31 BT  
A 6" Cedar bears S.70°E., 6.9 ft mkd: T31S R8W S5 BT  
A 12" hemlock bears N.33°E., 37.8 ft mkd: T30S R8W S32 BT.

Set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs

Set chaining nail at side center, nail and washer stamped "PLS 2830" at base of blaze, BT signs on front and back and painted red band for new BT.