TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7357)

Set a fir post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on West face; from which
A laurel, 6" dia., bears S.75°W., 25 lks., mkd: ¼ S BT.
A laurel, 8" dia., bears S.26°E., 22 lks., mkd: ¼ S BT.

Reported as not found, 9/1965 - DCSO, VRT - C.S. 53/67-27

BLM dependent resurvey by G. Steven Popken & James J. Carlson, Cadastral Surveyors, Group No. 866, surveyed April/May. 1975 - (DCSO Vol. 39 Page(s) 15831)

Point for the ¼ sec. cor. of secs. 29 & 30, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 22" in the ground with brass cap marked: T30S R8W

¼
S 30 | S 29
1975

from which
A fir, 10" dia., bears S.82½°E., 68 lks., mkd: ¼ S29 BT.
A fir, 18" dia., bears N.77½°W., 27 lks., mkd: ¼ S30 BT.

David Edwards -Crew: Brant Miller & Eric Sprinkle - 9/2025 - C.S. File 65/116-10

Found - Brass capped iron pipe per 1978 B.L.M. resurvey in good condition.
All previous bearing trees are gone.
New - A 9" dia. Fir scribed "¼ S29 BT" bears N.15°E., 9.5'
A 7" dia. Fir scribed "¼ S30 BT" bears S.66°W. 11.7'
5.5 ft steel posts are set 2 feet N.1°W.,and S.1°E., on line.
Declination - 15°