

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7357)

Set a fir post 4 ft. long, 4" sq., 24" in the ground for the corner to Secs. 19, 20, 29, & 30, marked T30S R8W S20 on the NE face, S29 on the SE face S30 on the SW face and S19 on the NW face. with 2 notches on the S and 5 notches on E edges, from which

- A sugar pine, 15" dia., bears N.25°E., 8 lks., mkd: T30S R8W S20 BT.
- A sugar Pine, 10" dia., bears S.48°E., 80 lks., mkd: T30S R8W S29 BT.
- A chincapin, 10" dia., bears S.65°W., 28 lks., mkd: T30S R8W S30 BT.
- A laurel, 8" dia., bears N.35°W., 4 lks., mkd: T30S R8W S19 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Ray Tracy & Mike Stone - Sept. 1965 - C.S. File 53/67-11

Found - Orig. now 28" S. Pine N.25°E., 5.3 ft., shows good scar.
Orig. 10", now 26" S. Pine S.48°E. 53.0 ft., prev. opened, shows good scribing.
No trace of Orig. SW nor NWS BTs

Set brass cap at cor. mkd: COUNTY SURVEYORS T30S R8W S19|S20
OFFICE 1965 S30|S29

New BTs- 6" Chinq. bears S.60°E., 21.7 scribed S29 T30S R8W CS BT.
6" Chinq. bears S.22°W., 14.2 ft. scribed S30 CS BT.
15" D.Fir bears N.83°W., 20.4 ft. scribed S19 T30S R8W CS BT.
10" D.Fir bears N.46°E., 49.3 ft. scribed S20 T30S R8W CS BT.

Note - Corner is on top of N - S ridge.

BLM dependent resurvey by Charles E. Akin, Jr., Cadastral Surveyor, under Group No. 795, surveyed Aug./Sept. 1972 - (DCSO Records Vol. 37 Page(s) 15226-7)

The cor. of secs. 19, 20, 29, and 30, pertetuated and recorded by Byron, in 1965, monumented with an iron post, 1" dia., firmly set, protruding 10", above ground, with brass cap (properly) mkd.
from which the original bearing trees

- A sugar pine, 29" dia., bears N.25°E., 8 lks., with healed blaze.

continued next page

PRIMARY CORNER DESCRIPTION Cor Secs 19, 20, 29, & 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A sugar pine, 26" dia., bears S.48°E., 82 lks., with scribe marks T30S R8 visible on opened blaze. (Record, 80 lks.)
and bearing trees mkd. by Byron, in 1965
A sugar pine, 13" dia., bears N.46°E., 77 lks., with scribe marks S R8W visible on partially healed blaze.
A chinquapin, 6" dia., bears S.60°E., 35½ lks. with scribe marks S29 T30S R8W CS BT visible on open blaze.
A chinquapin, 6" dia., bears S.22°W., 21 lks., with scribe marks S30 CS BT visible on open blaze.
A fir, 15" dia., bears N.83°W., 30½ lks., with healed blaze.

BLM dependent resurvey by G. Steven Popken & James J. Carlson, Cadastral Surveyors, Group No. 866, surveyed April/May. 1975 - (DCSO Vol. 39 Page(s) 15832)

The cor., of secs. 19,, 20, 29, and 30, perpetuated and recorded by Byron, in 1965, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.
from which the remains of the orig. BTs
A sugar pine, 28" dia., bears N.25°E., 8 lks., with healed blaze.
A sugar pine, 24" dia., bears S.48°E., 82 lks., no marks visible on opened blaze.
and BTs mkd by Byron
A sugar pine, 11" dia., bears N.46°E., 75½ lks., with scribe marks T30S R8W S20 CS BT visible on partially healed blaze.
A chinquapin, 7" dia., bears S.60°E., 33½ lks. with scribe marks T30S R8W S29 CS BT visible on healed blaze.
A chinquapin, 6" dia., bears S.22°W., 21 lks., with scribe marks S30 CS BT visible on partially healed blaze.
A fir, 17" dia., bears N.83°W., 30½ lks., with healed blaze.