

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7362)

Set a cedar post 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor., marked 1/4 S on West face; from which
 A chincapin, 8" dia., bears N.36°E., 6 lks., mkd: 1/4 S BT.
 A sugar pine, 22" dia., bears S.40°W., 33 lks. mkd: 1/4 S BT

Reported as not fd by DCSO VRT, 9/1965 - C.S. File 53/67-25

Bruce A. Shaner - For: Moore Mill & Lumber Co. - March 19, 1973 - M49-16

No orig. evidence found.
Set - Brass cap mkd: T30S R8W WM 1/4S S18 S17 1973
New BTs- 22" D.Fir scribed "1/4 S17 BT" bears N.14°E., 8.8 ft.
 14" D.Fir scribed "1/4 S18 BT" bears N.29 1/2°W., 6.3 ft.
Note - A well marked North-South properly line runs 7.0 ft, west if this corner.

BLM dependant resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2972, surveyed May 2020/Feb 2021 - (DCSO records Vol. 59 Page(s) 23968)

The 1/4 sec. cor. of secs. 17 and 18, reestablished by proportionate measurement by Shaner, in March 1973. There is no remaining evidence of the original cor., therefore this point is accepted as a careful & faithful reestablishment of the cor.; monumented with an iron post, 1 1/4" dia., firmly set, projecting 11" above ground, with brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Shaner
 A broken, decayed fir snag, 25" dia., bears N.13°E., 8.8 ft., with illegible scribe marks visible on partially healed blaze.
 A fir snag, 17" dia., bears N.32 1/4°W., 5.8 ft., with a healed blaze.
and new bearing trees
 A fir, 20" dia., bears N.37°E., 22.2 ft., mkd. 1/4 S17 BT.
 A fir, 5" dia., bears N.66 3/4°W., 23.1 ft., mkd. 1/4 S18 BT.
Each new BT has a 2 1/2"x 1/4" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.