

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17 & 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7362)  
-----  
Set a chincapin post 4 ft. long, 4" sq., 24" in the ground for the corner to Secs. 7, 8, 17, & 18, marked T30S R8W S8 on the NE face, S17 on the SE face S18 on the SW face and S7 on the NW face. with 4 notches on the South and 5 notches on East edges, from which  
A fir, 15" dia., bears N.15°E., 22 lks mkd: T30S R8W S8 BT  
A fir, 12" dia. bears S.58°E., 73 lks mkd: T30S R8W S17 BT  
A fir, 16" dia. bears S.35°W., 58 lks mkd: T30S R8W S18 BT  
A fir, 46" dia., bears N.50°W., 38 lks mkd: T30S R8W S7 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Stone - Sept. 1965 - C.S. File 53/67-10  
-----  
Found - Orig. 15" now 30" Fir N.15°E., 14.5 ft. shows frag. bark scribe, BT is alive.  
Orig. 12" now 15" Fir S.58°E., 48.2 ft. shows bark scribe in poor condition. BT is alive.  
Orig. 16" now 26" Fir S.25°W., 38.3 ft. shows as S.35°W., shows bark scribe in fair condition. BT Alive.  
Orig. 46" now 46" Fir snag N.50°W., 25.1 ft. no scribe found, bark gone.  
Set brass cap at cor mkd: COUNTY SURVEYORS T30S R8W S 7|S 8  
OFFICE 1965 S18|S17  
New BTs- 9" Chinq. S.70°W., 5.3 mkd: T30S R8W S18 CS BT.  
7" Chinq. N.2°W., 31.7 ft. mkd: T30S R8W S7 CS BT.  
6" W.Fir N.71°E., 40.7 ft. mkd: S8 CS BT.  
11" hemlock S.78°E., 37.5 ft mkd: T30S R8W S17 CS BT

Douglas Co. Surveyors Office - John M. Powell - Penley & Heritage - 9/10/1970 - C.S. File 53/67-5  
-----  
Found - 1965 County Surveyor brass cap, properly marked.  
9" Chinquapin now stob S.70°W. 5.3 ft scribe visible tree gone.  
7" now 9" Chinquapin N.2°W., 31.7 ft. scribe visible  
6" now 6" W.Fir N.71°E., 40.7 ft. scribe visible  
11" now 11" hemlock S.78°E., 37.5 ft. scribe visible, (this tree is in Sec. 17)  
New - 11" hemlock S.78°E., 37.5 ft. scribed T30S R8W S17 CS BT (reblazed & rescribed)  
22" hemlock S.70°W., 22.9 ft. scribed T30S R8W S18 CS BT

continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2972, surveyed May 2020/Feb 2021 - (DCSO records Vol. 59 Page(s) 23968-9)

-----

The cor. of secs. 7, 8, 17, and 18, perpetuated by Douglas County Surveyor's Office, in September 1965; and in 1970; monumented with an iron post, 1¼" dia., firmly set, projecting 3" above ground, with a brass cap (properly) mkd. from which the remains of the original bearing trees

A fir, 42" dia., bears N.15°E., 14.5 ft., no marks visible.

A roothole bears S.58°E., 48.2 ft., downhill of which is a down fir, 17" dia., no marks visible.

A decayed fir snag, 38" dia., bears N.50°W., 25.1 ft., with axe marks visible on bark.

and the BTs mkd. by Douglas County Surveyor's Office in 1965

A fir, 20" dia., bears N.69½°E., 40.5 ft., with a healed blaze.

A hemlock, 20" dia., bears S.79¾°E., 36.9 ft., with a healed blaze.

A chinquapin, 14" dia., bears N.2½°W., 31.3 ft., with a hollowed blaze.

and a BT mkd. by Douglas County Surveyor's Office in 1970

A hemlock, 30" dia., bears S.71½°W., 23.4 ft., with a healed blaze.