TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7364)

Set a cedar post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on West face; from which
A fir, 36" dia., bears S.78°E., 22 lks., mkd: ¼ S BT.
A fir, 36" dia., bears S.58°W., 27 lks., mkd: ¼ S BT.

Reported as not fd DCSO VRT - 10/12/1965 - C.S. File 53/67-31

Wm. C. Stiles - For: Moore Mill & Lbr. Co. June 21, 1967 - C.S. File 55/44 & M34-19

1/4 corner set at proportionate distance.
Set - 1"x30" I.Pipe set at the point for the corner, from which:
8" W.Fir bears N.36°08'12"W., 8.4 ft. mkd: ¼ S7 BT.
8" W.Fir bears N.87°33'43"E., 7.5 ft. mkd.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2972, surveyed May 2020/Feb 2021 - (DCSO records Vol. 59 Page(s) 23969-70)

The ¼ sec. cor. of secs. 7 and 8, reestablished by proportionate measurement by Stiles, in 1967. There is no remaining evidence of the original cor., therefore this point is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron pipe, 1¼" dia., firmly set, projecting 5" above ground, from which a BT mkd. by Stiles
A fir, 27" dia., bears N.34¼°W., 8.9 ft., with a healed blaze.
At the corner point Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over iron pipe, with brass cap mkd. T 30 S R 8 W

¼
S 7 | S 8
2021

and a new bearing tree
A chinquapin, 7" dia. bears N.7¾°E., 47.2 ft. mkd. ¼ S8 BT
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.