

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7365)

Set a cedar post 4 ft. long, 4" sq., 24" in the ground for the corner to Secs. 5, 6, 7, & 8, marked T30S R8W S5 on the NE face, S8 on the SE face S7 on the SW face and S6 on the NW face. with 5 notches on the South and East edges, from which
A chincapin, 15" dia., bears N.55°E., 6 lks., mkd: T30S R8W S5 BT.
A fir, 14" dia., bears S.56°E., 8 lks mkd: T30S R8W S8 BT
A fir, 15" dia., bears S.44°W., 72 lks mkd: T30S R8W S7 BT
A chincapin, 5" dia., bears N.50°W., 19 lks., mkd: T30S R8W S6 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - April & May 1965 - C.S. File 53/67-40

Found - Orig. 15" now 24" chinquapin N.55°E. 4.0 ft. now badly rotted stump, no scribe found.
Orig. 14" now 24" fir S.56°E., 5.8 ft. now snag, shows "T3RW S8BT" bark scribe in poor condition.
Orig. 15" now 24" fir S.44°W., 47.5 ft. turned out, no scribe.
No trace of other BT.
Set brass cap at cor. mkd: COUNTY SURVEYORS T30S R8W $\frac{S\ 6}{S\ 7} | \frac{S\ 5}{S\ 8}$
OFFICE 1965
New BTs- 16" cedar N.51°W., 28.4 ft mkd: T30S R8W S6 CS BT.
5" D.Fir S.82°W., 5.8 ft. mkd: S7 CS BT.
8" W.Fir S.18°E., 12.9 ft. mkd: T30S R8W S8 CS BT.
5" Chinquapin N.53°E., 8.4 ft. mkd: S5 CS BT.
Note - Corner is approximately 40.0 ft. south of old logging road on top of ridge.

BLM - Wayne Rogers, Bryan Seibold, & John Powell - 4/2/97 - C.S. 65/17-1

Found - 1¼" iron post with 1965 Co. Surveyors Brass cap
22" Fir snag, bears S.56°E., 8 lks.
10" Chinquapin, bears N.54°E., 13 lks. with healed blaze
10" Fir, bears S.18¼°E., 20 lks. with healed blaze
11" Fir, bears S.81½°W., 8½ lks. with healed blaze
New - 12" Fir, bears N.45½°W., 6 lks., mkd. T30S R8W S6 BT
corner is located 20' south of graveled road 20' wide BLM rd. No. 30-08-5.2

FD. OK by M. Smalley Aug. 2002, M137-50

cont.

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2972, surveyed May 2020/Feb 2021 - (DCSO records Vol. 59 Page(s) 23970-1)

The cor. of secs. 5, 6, 7, and 8, perpetuated by Douglas County Surveyor's Office, in April 1965; subsequently perpetuated by Rogers, in 1997; monumented with an iron post, 1¼" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd.

from which the remains of an original bearing tree

A decayed fir stump, size indeterminate, bears S.56°E., 5.3 ft., no marks visible.

and the remains of BTs mkd by Douglas Co Surveyor's Office

A roothole bears N.53½°E., 8.7 ft., alongside of which is a down chinquapin, size indeterminate, no marks visible.

A fir stump, 10" dia., bears S.18¾°E., 12.8 ft., with a healed blaze.

A fir stump, 12" dia., bears S.80°W., 5.6 ft., with a healed blaze.

and the remains of a bearing tree mkd. by Rogers

A fir stump, 15" dia., bears N.42°W., 4.0 ft., with a healed blaze.

and new accessories

A chinquapin, 13" dia., bears N.9¼°E., 88.7 ft., mkd. T30S R8W S5 BT.

An iron rod, 30" long, 5/8" dia., set 26" in the ground, for a reference monument, bears S.37°29'20"E., 19.27 ft., with aluminum cap mkd. RM T30S R8W S8 19.27 FT TO COR 2021 and an arrow pointing to the cor.

A fir, 5" dia., bears S.24¼°W., 59.1 ft., mkd. X BT.

A fir, 5" dia., bears N.18¾°W., 75.4 ft., mkd. T30S R8W S6 BT.

NAD 1983 (2011)

Latitude: 42°58'54.83" N. Longitude: 123°40'54.07" W.