TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7367-8)

Set a chincapin post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on West face for the ¼ sec. cor. from which
A fir, 15" dia., bears N.74°E., 33 lks., mkd: ¼ S BT.
A fir, 12" dia., bears S.62°W., 11 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - April/May 1965 - C.S. File 53/67-39

Found - Orig. 15" now 26" Fir N.74°E., 21.8 ft. turned out has "¼" bark scribe, appears very old.
12" now 15" fir stump S.62°W., 7.3 ft. badly decayed no scribe.
Set brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1965
T30S R8W ¼ S6|S5
New BTs- 9" W.Fir N.72°W., 10.0 ft. mkd: ¼ S6 CS BT.
6" W.Fir S.72°E., 21.0 ft. mkd: ¼ S5 CS BT
Corner lies on top spur sloping NE.

Mark Smalley - For: Roseburg Resources & Moore Mill - 8/2002 - M 137-50

Found - 1965 Douglas Co. Surveyors brass cap on an iron pipe
14" W.Fir N.74°W., 11.0' healed (rec. N.72°W. 10.0')
10" W.Fir S.72°E., 21.0' healed (rec. S.67°E. 20.3')
Scribed- 13" Chinquapin N.53°E., 20.0' "¼ BT"
9" W.Fir S.19½°W., 8.7' "¼ BT"