

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 239700

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 32 only, T29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6578)

Set ¼ sec. post, from which
A Fir 20" dia., bears S.89°E., 13 lks. dist.
A Fir 10" dia., bears N.77°E., 41 lks. dist.

BLM Resurvey by Dale T. Bedell and Bryan S. Seibold, Cadastral Surveyors - Under Group #1494, Surveyed July 1989/April 1993 - (DCSO records Vol. 50 Page(s) 19018-19)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
T29S R8W
¼ S32
T30S R8W
1993

from which
A Hemlock 5" dia., bears N.41½°E., 53 lks. dist. mkd. ¼ S32 BT.
A Cedar 14" dia., bears N.23½°W., 44 lks. dist. mkd. ¼ S32 BT.

FD. & used on BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1972, surveyed April/May 2001- (DCSO rec. Vol. 54 Page(s) 20961)