

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7355)

Set a cedar post 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor., marked 1/4 S on North face; from which
A laurel, 8" dia., bears N.28°E., 16 lks., mkd: 1/4 S BT.
A fir, 8" dia., bears S.45°W., 5 lks., mkd: 1/4 S BT.

Reported as not found, 9/1965 - DCSO, VRT - C.S. 53/67-29
Reported as not found, 3/1974 - Ron Stuntzner, M53-9

BLM dependent resurvey by G. Steven Popken & James J. Carlson, Cadastral Surveyors, Group No. 866, surveyed April/May. 1975 - (DCSO Vol. 39 Page(s) 15830)

Point for the 1/4 sec. cor. of secs. 29 & 32, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 1/2" dia., 24" in the ground with brass cap marked:

T30S R8W
1/4 S 29
 S 32
1975

from which

A fir, 22" dia., bears N.45 1/2°E., 35 lks., mkd: 1/4 S29 BT.
A hemlock, 6" dia., bears S.45°W., 40 lks., mkd: 1/4 S32 BT.